


3/4" DRIVE ADAPTERS

- › Use adapters to help increase or decrease drive end size.
- › Do not use hand adapters with power tools.
- › Do not over torque small sockets when using them with adapters on large drive tools.
- › Made of forged steel.
- › Size stamped on tool for easy identification.

| Product # | INCH | Overall Length (in) | Weight (lbs) |
|---------------|-----------------|---------------------|--------------|
| J07655 | 3/4" F x 1" M | 2-1/2 | 0.89 |
| J07656 | 1" F x 3/4" M | 2-7/8 | 1.42 |
| J7656 | 5/8" F x 3/4" M | 1-31/32 | 0.40 |

ASME B107.110-2012 



3/4" DRIVE IMPACT EXTENSIONS

- › Use extensions to gain access to fasteners in locations that would otherwise be difficult to reach.
- › Male square is oriented in-line with female squares for use with fixed head torque wrenches.
- › Full chamfer at drive opening (when applicable) for easy engagement with drive tools.
- › Drive end chamfer and four detents help provide quick positive engagement with drive tool on any of the socket drive walls.
- › Features two thru holes and a groove to accept a Proto retaining ring or pin or o-ring to help secure extension to the drive tool anvil.

| Product # | Overall Length (in) | Weight (lbs) |
|----------------|---------------------|--------------|
| J07565* | 5 | 1.48 |
| J07567 | 7 | 1.97 |
| J07568 | 10 | 2.73 |
| J07569 | 13 | 3.12 |

*This size not covered under ASME Standards

ASME B107.110-2012 



3/4" DRIVE IMPACT HEX BIT SOCKETS

- › Stamped size for easy reference.
- › Side locking hole.

| INCH | HEX | Overall Length (in) | Weight (lbs) | Repair Kit Part # |
|------|-------------------|---------------------|--------------|-------------------|
| 9/16 | J075909/16 | 3-3/4 | 0.96 | J075909/16RK |
| 5/8 | J075905/8 | 3-27/32 | 1.11 | J075905/8RK |
| 3/4 | J075903/4 | 4-3/8 | 1.75 | J075903/4RK |
| 7/8 | J075907/8 | 4-3/4 | 2.09 | J075907/8RK |
| 1 | J075901 | 5-13/64 | 2.59 | J075901RK |



