

WELDING BLANKETS & ROLLS

VELVET SHIELD®






Steiner's Velvet Shield® welding blankets are lightweight, soft, tough and flexible, providing incredible ease of use while withstanding high heat

Velvet Shield® blankets and rolls are made from a carbonized fiber and is the softest and toughest welding protection ever. Used for heavy duty welding, to protect from sparks, spatter, and light slag



316-18X18

HEAVY DUTY - Heavy sparks, spatter and slag

Material #	Description	Data Specs	Use	Rolls		Blanket	
				Width x Length	Part #	Sizes	Part #
316*	 <p>VELVET SHIELD Black Carbonized Fiber</p>	<p>Temp Rating 1800°F</p> <p>Weight 16 oz</p> <p>Thickness .15" - .20"</p>	<p>Sparks, spatter, and slag</p> <p>Soft, lightweight with excellent flexibility</p>	48"W X 50 yd	316-48	18" X 18"	316-18X18
				60"W X 50 yd	316-60	3' X 4'	316-3X4
				72"W X 50 yd	316-72	4' X 6'	316-4X6
				48"W X 50 ft	316-48RF	6' X 6'	316-6X6
						6' X 8'	316-6X8
		8' X 8'	316-8X8				
		8' X 10'	316-8X10				
		Custom	316-C				
317*	 <p>VELVET SHIELD HD Black Carbonized Fiber</p>	<p>Temp Rating 1800°F</p> <p>Weight 24 oz</p> <p>Thickness .25" - .30"</p>	<p>Sparks, spatter, and slag</p> <p>Soft, lightweight with excellent flexibility</p>	48"W X 50 ft	317-48RF	18" X 18"	317-18X18
				72"W X 50 ft	317-72RF	3' X 4'	317-3X4
						4' X 6'	317-4X6
						6' X 6'	317-6X6
						6' X 8'	317-6X8
		Custom	317-C				
371	 <p>SILICA Tan Silica Dioxide Cloth</p>	<p>Temp Rating 1800°F</p> <p>Melt 3000°F</p> <p>Weight 18 oz</p> <p>Thickness .030"</p>	<p>Sparks, spatter, and slag</p>	36"W X 50 yd	371-36	6' X 6'	371-6X6
				60"W X 50 yd	371-60	6' X 8'	371-6X8
						8' X 8'	371-8X8
						9' X 10'	371-9X10
						Custom	371-C
397*	 <p>Z-FLEX™ Black Vermiculite Coated Fiberglass</p>	<p>Temp Rating 1200°F</p> <p>Weight 26 oz</p> <p>Thickness .050"</p>	<p>Sparks, spatter, and slag</p>	40"W X 50 yd	397-40	6' X 6'	397-6X6
				60"W X 50 yd	397-60	6' X 8'	397-6X8
				72"W X 50 yd	397-72	8' X 8'	397-8X8
						8' X 10'	397-8X10
						10' X 10'	397-10X10
		Custom	397-C				
387*	 <p>Z-FLEX PLUS™ Tan Vermiculite Coated Fiberglass</p>	<p>Temp Rating 1200°F</p> <p>Weight 35 oz</p> <p>Thickness .080"</p>	<p>Sparks, spatter, and slag</p>	40"W X 50 yd	387-40	6' X 6'	387-6X6
				60"W X 50 yd	387-60	6' X 8'	387-6X8
				72"W X 50 yd	387-72	8' X 8'	387-8X8
						Custom	387-C

* Not recommended for stress relief