1/1.5/2 TON ENGINE CRANE

Dual pump piston design is 25% faster than other single pump designs. Folding ability stores away in small area.

- Dual pump pistons rapidly reach max height 25% faster than single pump designs
- Low profile 4.7" legs designed to fit under wide range of vehicle frames including sports cars
- 4 boom positions adjust for optimal reach based on required capacity
- Drop forged steel hook swivels 36° for ease of use and safety during operations, while chainless design eliminates sway during lifting
- Space saving design folds to conveniently store away in small footprint

5221 - 1 TON WITH DUAL PUMP PISTONS

5218 - 1.5 TON

5222 - 2 TON WITH DUAL PUMP PISTONS



| MODEL# | CAPACITY (TONS) BOOM POSITIONS: 1, 2, 3, 4 | MIN. HEIGHT (IN.) BOOM POSITIONS: 1, 2, 3, 4 | MAX. HEIGHT (IN.) BOOM POSITIONS: 1, 2, 3, 4 | BOOM LENGTH (IN.) BOOM POSITIONS: 1, 2, 3, 4 | Shipping Weight (LBS.) |
|--------|--|--|--|--|------------------------------|
| 5221 | 1/4, 1/2, 3/4, 1 | 0, 0, 4.7, 11 | 92.5, 87.2, 81.9, 76.6 | 49.6, 42.5, 35.4, 28.5 | 229 |
| 5218 | 3/8, 3/4, 1-1/8, 1-1/2 | 0, 0, 5.5, 11.75 | 96.5, 90.5, 84.5, 78.5 | 48, 41.5, 34, 27 | 210 |
| 5222 | 1/2, 1, 1-1/2, 2 | 0, 0, 5.5, 11.7 | 96.5, 90.5, 84.5, 78.5 | 48, 41.5, 34, 27 | 269 |

3/4 TON ENGINE SLING

Used with an engine crane to handle and position engines and heavy shop loads.

- Turn the bearing mounted hand crank to compensate for off-balanced loads or at a required angle for engine alignment
- · Four chains and mounting brackets included

5208A

| MODEL# | CAPACITY (TONS) | OVERALL LENGTH (IN.) | SHIPPING WEIGHT (LBS.) |
|--------|-----------------|----------------------|------------------------|
| 5208A | 3/4 Ton | 18 | 14.3 |



ENGINE TRANSVERSE BAR WITH ARM SUPPORT

Designed to support engine inside vehicle engine compartment for repairs of front wheel drive cars and replacement of motor mounts.

- The transverse bar can be used alone for 2 point applications or with adapter arm for applications requiring additional support
- Two 14" long adjustable hook screws and 1/8" diameter steel cable 38" long included
- Fully adjustable transverse bar and adapter arm for multiple engine configurations
- Transverse bar extends from 34.5" to 61"
- Shipping Weight: 25.24 Lbs.



