



6" DUAL ACTION ORBITAL AIR SANDER

- Rotary and orbital motion for rapid removal as well as fine finishing
- Built-in regulator for precise speed control
- Insulated grip for additional comfort

SX203N

SPECS	SIZE
Pad Size (in.)	6
Free Speed (RPM)	10,000
Weight (lbs.)	4.5
Length (in.)	9.25
Average Air Consumption (CFM)	4
Air Inlet Thread-Size (NPTF)	1/4
Min. Hose Size (I.D.)	3/8
Sound Level (dBA)	91

Includes: 6" bonded sanding pad
6" Replacement pad - 6PSAPAD



6" RANDOM ORBITAL SANDER

- Lowest profile in its class for great balance and control
- Lightweight and quiet
- Great tool for finishing work

SX7625

SPECS	SIZE
Pad Size (in.)	6
Orbit (in.)	3/32
Free Speed (RPM)	12,000
Weight (lbs.)	1.98
Length (in.)	7.3
Average Air Consumption (CFM)	2
Air Inlet Thread-Size (NPTF)	1/4
Min. Hose Size (I.D.)	3/8

DUAL PISTON STRAIGHT LINE AIR SANDER

- Dual piston design provides stall free performance
- 100% Needle Bearing construction is designed for longer life
- Automatic release trigger for positive stop action

SX288C



SPECS	SIZE
Pad Size (in.)	16 x 2.5
Free Speed (RPM)	2,500
Weight (lbs.)	6.6
Length (in.)	16.13
Average Air Consumption (CFM)	8
Air Inlet Thread-Size (NPTF)	1/4
Min. Hose Size (I.D.)	3/8
Sound Level (dBA)	93

Replacement pad assembly - RS28635A