

Since 1984, we've led the market with our solution-based designs and quality materials. All of our Impact Sockets (low-profile, standard, deep, hex drivers, universal joint, specialty, and extensions/adapters) are backed by an industry-leading warranty, so you can rest easy knowing your sockets are guaranteed to perform.

IMPACT SOCKETS

HIGHEST QUALITY. HIGHEST STANDARDS.

RADIUSED CORNERS

Focuses impact on fastener's flat surfaces, increasing torque and reducing wear and rounding to the fastener.

DURABLE CR-MO STEEL

Precision manufactured with chrome-molybdenum steel for high-impact applications.

HEAT TREATED / TEMPERED

Sockets are first heat treated to increase hardness and then tempered to maximize durability.





SPECIALTY SOCKETS

Every job has its own challenges. We offer a wide selection of specialty sockets to handle anything the job calls for.

METRIC



DRIVE





SAE




NO-SKIP SIZE SPECTRUM

Sunex Impact Socket Sets include every size in the specification range: Largest to smallest, and everything in between.

3/4" DRIVE METRIC **INDIVIDUAL SOCKETS**


SIZE	STANDARD	DEEP	12 POINT Thin Wall
METRIC	MODEL	MODEL	MODEL
15mm			415MZT
16mm			416MZT
17mm			417MZT
18mm			418MZT
19mm	419M	419MD	419MZT
20mm	420M	420MD	420MZT
21mm	421M	421MD	421MZT
22mm	422M	422MD	422MZT
23mm	423M	423MD	423MZT
24mm	424M	424MD	424MZT
25mm	425M	425MD	425MZT
26mm	426M	426MD	426MZT
27mm	427M	427MD	427MZT
28mm	428M	428MD	428MZT
29mm	429M	429MD	429MZT
30mm	430M	430MD	430MZT
31mm	431M	431MD	
32mm	432M	432MD	432MZT
33mm	433M	433MD	433MZT
34mm	434M	434MD	
35mm	435M	435MD	435MZT
36mm	436M	436MD	436MZT
37mm			
38mm	438M	438MD	438MZT
39mm		439MD	
40mm	440M	440MD	440MZT
41mm	441M	441MD	
42mm	442M	442MD	
43mm	443M	443MD	
44mm	444M	444MD	
45mm	445M		
46mm	446M	446MD	
47mm	447M	447MD	
48mm	448M	448MD	
49mm	449M	449MD	
50mm	450M	450MD	
52mm	452M	452MD	
54mm	454M		
55mm	455M	455MD	
56mm	456M		
60mm	460M	460MD	
63mm	463M		
65mm	465M	465MD	




IMPACT SOCKETS - SPECIFICATIONS

T1 T2

Α



В



3/4" DR. STANDARD 6 POINT METRIC

ITEM	SIZE	SHAPE	D	D	T1	T2	L1	L
419M	19mm	Α	30	38	16	25	28	50
420M	20mm	Α	31	38	16	25	28	52
421M	21mm	Α	32	38	18	25	28	52
422M	22mm	Α	34	38	18	25	28	52
423M	23mm	Α	35	38	18	25	28	52
424M	24mm	Α	36	38	18	25	28	52
425M	25mm	В	/	38	18	25	/	52
426M	26mm	В	/	40	18	25	/	52
427M	27mm	В	/	40	18	25	/	52
428M	28mm	В	/	42	18	25	/	52
429M	29mm	В	/	42	18	25	/	52
430M	30mm	В	/	44	18	25	/	52
431M	31mm	В	/	44	18	25	/	52
432M	32mm	В	1	44	22	25	/	56
433M	33mm	С	47	44	22	25	23	56
434M	34mm	С	48	44	22	25	23	56
435M	35mm	С	50	44	22	25	23	56
436M	36mm	С	51	44	22	25	23	56
438M	38mm	С	53	44	22	25	23	56
440M	40mm	С	56	44	26	31	25	62
441M	41mm	С	58	44	26	31	25	62
442M	42mm	С	61	44	26	31	25	62
443M	43mm	С	63	44	27	31	25	63
444M	44mm	С	65	44	27	31	25	63
445M	45mm	С	66	44	27	31	25	63
446M	46mm	С	67	44	27	31	25	63
447M	47mm	С	68	44	32	31	25	68
448M	48mm	С	69	44	32	31	25	68
449M	49mm	С	70	44	34	31	25	70
450M	50mm	С	71	54	35	32	25	72
452M	52mm	С	74	54	35	32	25	72
454M	54mm	С	77	54	35	32	25	72
455M	55mm	С	77	54	35	34	25	74
456M	56mm	С	80	54	35	34	25	74
460M	60mm	С	84	54	35	35	25	75
465M	65mm	С	88	54	35	38	25	78