

## BOTTLE JACK MODELS

- 4902A 2 TON**
- 4904A 4 TON**
- 4906A 6 TON**
- 4908A 8 TON**

Used for lifting, pushing, bending, and straightening applications in the automotive, industrial, agricultural, recreation, and construction markets.

### FEATURES:

- > Ductile iron base for added strength
- > Electrostatic paint for rust prevention
- > Heat treated extension screw increases low height to get full use of ram travel
- > Hydraulic bypass system prevents over extension of ram
- > Two-piece slip fit handle for controlling the release valve and pumping the jack
- > Model 4908A includes a grab handle for carrying a heavier jack



## BOTTLE JACK MODELS

- 4912A 12 TON**
- 4913A 12 TON SHORT HEIGHT**
- 4920A 20 TON**
- 4923A 20 TON SHORT HEIGHT**
- 4930A 30 TON**
- 4950B 50 TON**

Used for the same applications of the lower capacity bottle jacks but also heavy duty trucks, farm equipment, building construction, mining, mobile home setup, oil field, and power sources for manufacturers' products.

### FEATURES:

- > Ductile iron base for added strength. Models 4930A and 4950B have solid steel bases
- > Electrostatic paint for rust prevention
- > Heat treated extension screw increases low height to get full use of ram travel in 12 and 20 ton models only
- > Hydraulic bypass system prevents over extension of ram
- > Model 4920A includes an overload valve to prevent being used beyond its rated capacity
- > Two-piece slip fit handle on models 4912A and 4920A, three-piece slip fit handle on the remaining models for controlling the release valve and pumping the jack
- > All models include a grab handle for carrying and positioning purposes



MODEL #	Capacity (tons)	Low Height (in.)	Ram Travel (in.)	Ext. Screw Travel (in.)	Max. Height (in.)	Base (in.)	Shipping Weight (lbs.)
4902A	2	7.25	4.75	2	14	3.5 x 3.75	6
4904A	4	7.75	5	2.25	15	3.6 x 4	7.5
4906A	6	8.5	5.75	2.75	17	3.8 x 4.5	10.2
4908A	8	9	6.25	3.25	18.5	4 x 4.75	12.7
4912A	12	9.125	6.125	3.25	18.5	4.5 x 5.25	16.4
4913A	12	6	3.75	1.75	11.5	5.15 x 5.5	14
4920A	20	9.5	6.56	2.43	18.5	5.75 x 6	24.6
4923A	20	6.62	3.87	1.37	11.87	6.1 x 6.25	20.6
4930A	30	11.2	7.07	-	18.27	6 x 7.75	47.74
4950B	50	11.79	7.07	-	18.86	7 x 8.75	67.54