UNDER HOIST COMPONENT STAND MODEL 3320A

- Designed to support vehicle components
- Adjusts from 54.5" to 80.5" •
- Includes foot operated pump for extra lift
- Bearing included for smooth operation •
- 12" diameter base
- Ship weight 36 lbs

2 TON HIGH LIFT UNDER HOIST STABILIZING STAND **MODEL 3315A**

- Designed to support vehicle components only •
- Ideal for exhaust and suspension work
- Adjusts from 55" to 85.5"
- Bearing included for smooth operation
- Easily disassembles for storage •
- 24"x24"x24" base •
- Ship weight 44 lbs

2 TON UNDER HOIST STABILIZING STAND . **MODEL 3233A**

- Designed to support vehicle components only
- Adjusts from 66.5" to 73"
- Includes adjusting screw for easier load positioning
- Bearing included for smooth operation
- 21"x21"x21" base
- Ship weight 26 lbs

•50 TON TRAILER STABILIZING STAND MODEL 3318

- 100,000 lb static load capacity
- 45,000 lb lifting capacity
- Can be used to stabilize loaded and unloaded trailers when not connected to trucks
- Adjusts from 39" to 51"
- Pivoting and reversible ratchet head levels trailers on uneven ground
- Wide 14" diameter base for added stability
- Removable pipe handle
- Ship weight 157 lbs



Meets OSHA requirements for stabilizing loaded and

•7.5 TON FIXED HIGH TRUCK STAND MODEL 3342SD

- adjustment by screw
- and portability
- Ship weight 134 lbs



7.5 TON FIXED HIGH TRUCK STAND ····· MODEL 3344SD

- Adjustable height range from 36" to 54"
 - Seventeen 1" height adjustments

 - and portability
 - Ship weight 103 lb



16.5 TON FIXED HIGH TRUCK STAND MODEL 3340SD

- adjustment by screw
- and portability
- - - Ship weight 324 lbs



20 TON WIDE STANCE TRUCK RAMPS MODEL 3420ASD

- Long retractable handle
- Wheels ease movement and stores easily out of the way
- Suitable for large truck tires up to 16" maximum width
- Comes with rubber nonskid pad to prevent slippage
- 20 ton capacity per pair
- Frame = 47" L x 18.25" W x 9.25" H
- Overall length = 51"
- Tread Width = 16"
- Ships one pair in wooden crate
- Ship weight 396 lbs. per pair



AFF

unloaded trailer



• Adjustable height range from 57" to 82" • Twenty one 1" height adjustments with 4" fine

• Spring loaded casters allow for ease of positioning

• Non-skid rubber saddle pad for secure placement Spring loaded tower for easy height adjustment



• Non-skid rubble saddle for secure placement Spring loaded casters for ease of positioning



• Adjustable height range from 57" to 82" • Twenty one 1" height adjustments with 4" fine

Spring loaded casters allow for ease of positioning

Non-skid rubber saddle pad for secure placement Spring loaded tower for easy height adjustment







Adjustable Height

