

M12 FUEL

1/2" Hammer Drill/Driver Kit 2504-22 (2504-20 Tool-Only)

| Specifications: | | |
|-----------------|--|--|
| Peak Torque | 350 in-Ibs | |
| RPM | 0 – 1,700 | |
| BPM | 0 - 25,500 | |
| Chuck Type | 1/2" Metal Single Sleeve – Ratcheting Chuck | |
| Length / Weight | 6.6" / 2.3 lbs | |

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack. (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

M12[™] 3/8[∥] Hammer **Drill/Driver Kit**

2408-22 (2408-20 Tool-Only) Specifications:

| Sp | ec | ITIC | aτ | 101 | ns |
|----|----|------|----|-----|----|
| | | | | | |

| Peak Torque | 275 in-lbs |
|-----------------|--------------------------|
| RPM | 0 - 400 / 0 - 1,500 |
| BPM | 0 – 22,500 |
| Chuck Type | 3/8" Metal Single Sleeve |
| Length / Weight | 7.5" / 2.7 lbs |

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs. Belt Clip, Charger, Carrying Case

M12FUEL 1/2" Drill/Driver Kit 2503-22 (2503-20 Tool-Only)

| Specifications: | | |
|-----------------|--|--|
| Peak Torque | 350 in-lbs | |
| RPM | 0 – 1,700 | |
| Chuck Type | 1/2" Metal Single Sleeve – Ratcheting Chuck | |
| Length / Weight | 6.6" / 2.3 lbs | |

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

MIZFUEL Installation **Drill/Driver Kit** 2505-22 (2505-20 Tool-Only)

Specifications: 200

| Attachments | 3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle |
|--------------|---|
| RPM (2-Mode) | 0 - 400 / 0 - 1,600 |
| Max Torque | 300 in-lbs |
| | |

Length / Weight 5.1" / 2.0 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, (4) Attachments (3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle), Belt Clip, Charger, Compartmentalized Contractor Bag

M12[™] 3/8[″] **Drill/Driver Kit**

2407-22 (2407-20 Tool-Only) **C**rocificati

| Specifications: |
|-----------------|
|-----------------|

13

| Peak Torque | 275 in-Ibs |
|-----------------|--------------------------|
| RPM | 0 - 400 / 0 - 1,500 |
| Chuck Type | 3/8" Metal Single Sleeve |
| Length / Weight | 7.4" / 2.5 lbs |

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



| M12 [™] 3/8 [∥] Right Angle Drill/Driver Kit |
|---|
| |

2415-21 (2415-20 Tool-Only) Specifications:

| Peak Torque | 100 in-lbs |
|-----------------|-----------------------------|
| RPM | 0 - 800 |
| Clutch Settings | 11 Settings plus Drill Mode |
| Chuck Type | 3/8" Single Sleeve |
| Head Profile | 3.8" |
| Weight | 2.4 lbs |
| | |

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

| M12 EUEL 1/4" Hex 2-Speed Screwdriver Kit 2402-22 (2402-20 Tool-Only) Specifications: | | |
|---|-----------------|-----------------------|
| | Peak Torque | 325 in-Ibs |
| | RPM | 0 - 450 / 0 - 1,700 |
| | Chuck Type | 1/4" Hex Quick Change |
| | Length / Weight | 6.6" / 2.0 lbs |

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



| epoolineationel | | |
|-----------------|---------------------|--|
| Peak Torque | 275 in-lbs | |
| RPM | 0 - 400 / 0 - 1,500 | |

Chuck Type 1/4" Hex Quick Change Length / Weight 6.8" / 1.8 lbs Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case



| RPM | 0 – 500 |
|-----------------|-----------------------|
| Chuck Type | 1/4" Hex Quick Change |
| Length / Weight | 6.5" / 2.0 lbs |
| | |

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Soft Carrying Case



| | Fastening Torque | 1,300 in-lbs |
|--|------------------|-----------------------|
| | IPM | 0-4,000 |
| | RPM | 0-3,300 |
| | Chuck Type | 1/4" Hex Quick Change |
| | Length / Weight | 5.1" / 1.8 lbs |

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs. Belt Clip, Charger, Carrying Case



MIZEUEL **SURGE[™] 1/4[™] Hex Hydraulic Driver Kit**

2551-22 (2551-20 Tool-Only)

| Specifications: | |
|-------------------------------|-----------------------|
| Sustained Fastening Torque | 450 ft-lbs |
| IPM | 0 - 3,400 |
| RPM | 0 – 3,200 |
| Chuck Type | 1/4" Hex Quick Change |
| Length / Weight | 5.2" / 2.4 lbs |
| | |

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Contractor Bag

M12[™] 1/4[¶] Hex Impact **Driver Kit**

2462-22 (2462-20 Tool-Only) Specifications: Fastening Torque

| r asterning rorque | 1,000 111 105 |
|--------------------|----------------|
| IPM | 0 - 3,300 |
| RPM | 0 – 2,500 |
| Chuck Type | 1/4" Hex |
| Lenath / Weight | 6.5" / 2.3 lbs |

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

1 000 in-lbs

M12[™] 1/4[¶] Hex Right Angle **Impact Driver Kit** 2467-21 (2467-20 Tool-Only)

Specifications:

| | - |
|------------------|------------|
| Fastening Torque | 600 in-lbs |
| IPM | 0 – 3,300 |
| RPM | 0 - 2,450 |
| Chuck Type | 1/4" Hex |
| Head Profile | 1.4" |
| Weight | 2.6 lbs |
| | |

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

MZFUEL

1/2" Stubby Impact Wrench Kit 2555-22, 2555P-22 (2555-20 Tool-Only)

Specifications:

| opcomoutionsi | |
|-----------------|--------------------|
| Peak Torque | 250 ft-lbs |
| IPM | 0 – 3,200 |
| RPM | 0 - 2,700 |
| Anvil Type | 1/2" Friction Ring |
| Length / Weight | 4.9" / 2.1 lbs |

Includes: 2555-22 1/2" Stubby Impact Wrench; 2555P-22 1/2" Stubby Impact Wrench w/ Pin Detent; All Kits Include: (1) M12™ REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case













MIZELEL

3/8" Stubby Impact Wrench Kit

2554-22 (2554-20 Tool-Only) **Specifications:**

| - | |
|-----------------|--------------------|
| Peak Torque | 250 ft-lbs |
| IPM | 0-3,200 |
| RPM | 0 - 2,700 |
| Anvil Type | 3/8" Friction Ring |
| Length / Weight | 4.8" / 2.1 lbs |



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12FUEL

1/4" Stubby Impact Wrench Kit

2552-22 (2552-20 Tool-Only) Specifications:

| opeenieatiene | |
|-----------------|--------------------|
| Peak Torque | 100 ft-lbs |
| IPM | 0 - 4,300 |
| RPM | 0 - 3,200 |
| Anvil Type | 1/4" Friction Ring |
| Length / Weight | 5.1" / 1.8 lbs |



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12 FUEL

3/8" Impact Wrench Kit

2454-22 (2454-20 Tool-Only)

| Peak Torque | 117 ft-lbs |
|-----------------|-----------------------|
| IPM | 0 – 3,500 |
| RPM (2-Mode) | 0 - 1,200 / 0 - 2,650 |
| Anvil Type | 3/8" Friction Ring |
| Length / Weight | 6.5" / 2.4 lbs |



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 3/8[¶] Impact Wrench Kit 2463-22 (2463-20 Tool-Only)

Specifications:

| Peak Torque | 100 ft-lbs |
|-----------------|--------------------|
| IPM | 0 - 3,300 |
| RPM | 0 - 2,500 |
| Anvil Type | 3/8" Friction Ring |
| Length / Weight | 6.5" / 2.3 lbs |



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 1/4[¶] Impact Wrench Kit

2461-22 (2461-20 Tool-Only) Specifications:

| specifications: | | |
|-----------------|--------------------|--|
| Peak Torque | 38 ft-lbs | |
| IPM | 0 - 3,800 | |
| RPM | 0 – 2,500 | |
| Anvil Type | 1/4" Friction Ring | |
| Length / Weight | 6.0" / 2.1 lbs | |
| | | |





14