


DRIVEN TO OUTPERFORM.

M12 FUEL[™] is engineered for the most demanding tradesmen in the world. M12 FUEL[™] delivers unrivaled performance in a compact structure and features three MILWAUKEE[®] exclusive innovations – the POWERSTATE[™] Brushless Motor, REDLITHIUM[™] Battery Pack and REDLINK PLUS[™] Intelligence Hardware and Software – that deliver unmatched power, run-time and durability.

Simply put, M12 FUEL[™] is best-in-class, full-circle technology that drives, protects and powers your cordless tools beyond the rest.







POWERSTATE[™] BRUSHLESS MOTOR

- MILWAUKEE[®] Designed and Built Brushless Motor
- Outperforms All Leading Competitors
- Up to 10X Longer Motor Life





- Most Advanced Electronic System
- Total System Communication with
- Built-In Fuel Gauge Displays Remaining Charge





M12 FUEL

1/2" Hammer Drill/Driver Kit 2504-22 (2504-20 Tool-Only)

Specifications:			
Peak Torque	350 in-Ibs		
RPM	0 - 1,700		
BPM	0 - 25,500		
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck		
Length / Weight	6.6" / 2.3 lbs		

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack. (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

M12[™] 3/8[¶] Hammer **Drill/Driver Kit**

2408-22 (2408-20 Tool-Only) Specifications:

эþ	e			a	 U	5	-
_		_					_

Peak Torque	275 in-Ibs
RPM	0 - 400 / 0 - 1,500
BPM	0 – 22,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.5" / 2.7 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

M12FUEL 1/2" Drill/Driver Kit 2503-22 (2503-20 Tool-Only)

Specifications:				
Peak Torque	350 in-Ibs			
RPM	0 – 1,700			
Chuck Type	1/2" Metal Single Sleeve – Ratcheting Chuck			
Length / Weight	6.6" / 2.3 lbs			

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Carrying Case

MIZFUEL Installation **Drill/Driver Kit** 2505-22 (2505-20 Tool-Only)

Specifications:

Max Torque	300 in-Ibs	
RPM (2-Mode)	0 - 400 / 0 - 1,600	
Attachments	3/8" Metal Chuck, 1/4" Hex, Offset and F	Right Angle

Length / Weight 5.1" / 2.0 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, (4) Attachments (3/8" Metal Chuck, 1/4" Hex, Offset and Right Angle), Belt Clip, Charger, Compartmentalized Contractor Bag

M12[™] 3/8[″] **Drill/Driver Kit**

2407-22 (2407-20 Tool-Only)

Peak Torque	275 in-Ibs
RPM	0 - 400 / 0 - 1,500
Chuck Type	3/8" Metal Single Sleeve
Length / Weight	7.4" / 2.5 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 3/8["] Right **Angle Drill/Driver Kit** 2415-21 (2415-20 Tool-Only)

2415-21 (2415-20 1001-0	Jiliy)
Specifications:	
De els Tesses	100 1

Peak Torque	100 in-Ibs
RPM	0 - 800
Clutch Settings	11 Settings plus Drill Mode
Chuck Type	3/8" Single Sleeve
Head Profile	3.8"
Weight	2.4 lbs

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

1/4" Hex 2-Speed Screwdriver Kit 2402-22 (2402-20 Tool-Only) Specifications:				
Peak Torque	325 in-Ibs			
RPM	0 - 450 / 0 - 1,700			
Chuck Type	1/4" Hex Quick Change			
Length / Weight	6.6" / 2.0 lbs			

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case



	Peak Torque	275 in-lbs
	RPM	0 - 400 / 0 - 1,500
	Chuck Type	1/4" Hex Quick Change

Length / Weight 6.8" / 1.8 lbs **Includes:** (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

Kit
ly)
75 in-Ibs
- 500


	0 000
Chuck Type	1/4" Hex Quick Change
Length / Weight	6.5" / 2.0 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Soft Carrying Case



	Fastening Torque	1,300 in-lbs
	IPM	0-4,000
	RPM	0-3,300
	Chuck Type	1/4" Hex Quick Change
	Length / Weight	5.1" / 1.8 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case





MIZEUEL **SURGE[™] 1/4[™] Hex Hydraulic Driver Kit**

2551-22 (2551-20 Tool-Only) Specifications:

Sustained Fastening Torque	450 ft-lbs
IPM	0 - 3,400
RPM	0 - 3,200
Chuck Type	1/4" Hex Quick Change
Length / Weight	5.2" / 2.4 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Contractor Bag

M12[™] 1/4[¶] Hex Impact **Driver Kit**

2462-22 (2462-20 Tool-Only) Specifications: Eastening Torque

Tasterning Torque	1,000 111-103
IPM	0 - 3,300
RPM	0 - 2,500
Chuck Type	1/4" Hex
Length / Weight	6.5" / 2.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] CP1.5 Battery Packs, Belt Clip, Charger, Carrying Case

1 000 in-lbs

M12[™] 1/4[¶] Hex Right Angle **Impact Driver Kit** 2467-21 (2467-20 Tool-Only)

Specifications:

Fastening Torque	600 in-lbs	
IPM	0 – 3,300	
RPM	0 – 2,450	
Chuck Type	1/4" Hex	
Head Profile	1.4"	
Weight	2.6 lbs	

Includes: (1) M12[™] REDLITHIUM[™] CP1.5 Battery Pack, Charger, Soft Carrying Case

MZFUEL

1/2" Stubby Impact Wrench Kit 2555-22, 2555P-22 (2555-20 Tool-Only)

Specifications

Specifications	
Peak Torque	250 ft-lbs
IPM	0-3,200
RPM	0 - 2,700
Anvil Type	1/2" Friction Ring
Length / Weight	4.9" / 2.1 lbs

Includes: 2555-22 1/2" Stubby Impact Wrench; 2555P-22 1/2" Stubby Impact Wrench w/ Pin Detent; All Kits Include: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case











































MIZELEL

3/8" Stubby Impact Wrench Kit

2554-22 (2554-20 Tool-Only) Specifications:

-	
Peak Torque	250 ft-lbs
IPM	0-3,200
RPM	0 - 2,700
Anvil Type	3/8" Friction Ring
Length / Weight	4.8" / 2.1 lbs



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12FUEL

1/4" Stubby Impact Wrench Kit

2552-22 (2552-20 Tool-Only) Specifications:

epeemeanenen		
Peak Torque	100 ft-lbs	
IPM	0 - 4,300	
RPM	0 - 3,200	
Anvil Type	1/4" Friction Ring	
Length / Weight	5.1" / 1.8 lbs	



Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Battery Pack, (1) M12[™] REDLITHIUM[™] CP2.0 Battery Pack, Belt Clip, Charger, Soft Carrying Case

M12 FUEL

3/8" Impact Wrench Kit

2454-22 (2454-20 Tool-Only)

Peak Torque	117 ft-lbs
IPM	0 – 3,500
RPM (2-Mode)	0 - 1,200 / 0 - 2,650
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.4 lbs



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 3/8[¶] Impact Wrench Kit 2463-22 (2463-20 Tool-Only)

Specifications:

Peak Torque	100 ft-lbs
IPM	0 - 3,300
RPM	0 - 2,500
Anvil Type	3/8" Friction Ring
Length / Weight	6.5" / 2.3 lbs



Includes: (2) M12[™] REDLITHIUM[™] CP2.0 Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 1/4[¶] Impact Wrench Kit

2461-22 (2461-20 Tool-Only) Specifications:

specifications:		
Peak Torque	38 ft-lbs	
IPM	0 - 3,800	
RPM	0 – 2,500	
Anvil Type	1/4" Friction Ring	
Length / Weight	6.0" / 2.1 lbs	





14