

M18FUEL

3/8["] Impact Wrench w/ Friction Ring w/ ONE-KEY[™] Kit

2758-22, 2758-22CT (2758-20 Tool-Only) Specifications:

specifications:	
Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 - 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	5.9" / 4.2 lbs

Includes: 2758-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2758-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

M18 FUEL 3/8" Compact Impact Wrench

w/ Friction Ring Kit

2854-22, 2854-22CT (2854-20 Tool-Only)

Specifications:	
-----------------	--

Fastening Torque	250 ft-lbs
Nut-Busting Torque	250 ft-lbs
IPM	0 - 3,500
RPM	0 - 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: 2854-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs: 2854-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18[™] 3/8[¶] Compact Impact Wrench Kit

2658-22, 2658-22CT (2658-20 Tool-Only)

Sp	ecit	icat	lion	Si

Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 - 3,350
RPM	0 – 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

Includes: 2658-22 (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs; 2658-22CT (2) M18[™] REDLITHIUM[™] CP1.5 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18FUEL

1/2" Mid-Torque Impact Wrench w/ Pin Detent Kit 2962P-22 (2962P-20 Tool-Only)

Specifications:

opeomoutionsi	
Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,500
RPM	0 – 2,400
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	4.8" / 3.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18 U U U 1/2" Mid-Tor w/ Friction F 2962-22 (2962-20 Tool	_
Specifications:	1
Fastening Torque	650 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 - 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.1 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

™®FUEL 3/8" Mid-Tor w/ Friction F	que Impact Wrenc
2960-22, 2960-22CT (2	
Specifications:	
Fastening Torque	600 ft-lbs
Nut-Busting Torque	550 ft-lbs
IPM	0 – 3,100
RPM	0 – 2,575
DRIVE CONTROL™	4-Mode w/ Auto Shut-Off Mode & Bolt Removal Mode
Length / Weight	6.0" / 5.0 lbs

Includes: 2960-22 (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs; 2960-22CT (2) M18[™] REDLITHIUM[™] CP2.0 Battery Packs;

All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

M18 CUEU 1" D-Handle H Impact Wrent w/ ONE-KEY 2868-22HD (2868-20 Too Specifications:	ch Kit	-
Fastening Torque	1,900 ft-lbs	
Nut-Busting Torque	2,000 ft-lbs	REDLI
IPM	0 - 1,440	HIGH OUTP
RPM	0 – 1,200	
DRIVE CONTROL™	4-Mode (Customizable)	

Length / Weight 17.94" / 21 lbs

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag

M18 CUEU 1" D-Handle Torque Impa w/ ONE-KEY 2869-22HD (2869-20 T Specifications:	™ Kit see	
Fastening Torque	1,900 ft-lbs	
Nut-Busting Torque	2,000 ft-lbs	REDLITHIUM
IPM	0 - 1,440	HIGH OUTPUT HD120
RPM	0 – 1,200	(
DRIVE CONTROL™	4-Mode (Customizable)	
Length / Weight	23.2" / 27.2 lbs	

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] HD12.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag



M18 FUEL **1" High Torque Impact** Wrench w/ ONE-KEY[™] Kit

2867-22 (2867-20 Tool-Only) **Specifications:**

Fastening Torque	1,500 ft-lbs
Nut-Busting Torque	1,800 ft-lbs
IPM	0 - 2,450
RPM	0 – 1,650
DRIVE CONTROL [™]	4-Mode (Customizable)
Length / Weight	10.9" / 13 lbs

Includes: (2) M18[™] REDLITHIUM[™] HIGH OUTPUT[™] XC8.0 Battery Packs, Tool-Free Adjustable Handle, Lanyard Loop, Rapid Charger, Contractor Bag

M18 FLEL

3/4" High Torque Impact Wrench w/ Friction Ring w/ ONE-KEY[™] Kit

2864-22 (2864-20 Tool-Only)

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.6" / 7.9 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

M18[™] 3/4[¶] High Torque Impact Wrench w/ Friction Ring Kit

2664-22 (2664-20 Tool-Only) **Specifications:**

opeeniedlienei	
Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Lenath / Weight	9.0" / 6.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

MIBFUEL **1/2" Ext. Anvil Controlled Torque** Impact Wrench w/ ONE-KEY[™] Kit

2769-22 (2769-20 Tool-Only) **Specifications:**

Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 - 2,400
RPM	0 – 1,800
DRIVE CONTROL [™]	4-Mode (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	10.1" / 5.8 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Contractor Bag







M18FUEL

1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY[™] Kit

2862-22 (2862-20 Tool-Only) Specifications:

opcomoutionsi	
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 - 2,400
RPM	0 - 1,800
DRIVE CONTROL™	4-Mode (Customizable)
Length / Weight	8.1" / 7.2 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



3

M18 FUEL 1/2" High Torque Impact Wrench w/ Pin Detent Kit

2766-22 (2766-20 Tool-	Only)
Specifications:	
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 - 2,400
RPM	0 - 1,850
DRIVE CONTROL™	4-Mode w/ Bolt Removal Mode
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

M18[™] 1/2[¶] High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only) Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 – 2,200
RPM	0 – 1,900
Length / Weight	8.9" / 6.7 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case





2863-22 (2863-20 Tool-Only) **Specifications:**

1,000 ft-lbs
1,400 ft-lbs
0 – 2,100
0 – 1,750
4-Mode (Customizable)
8.4" / 7.6 lbs



Includes: (2) M18[™] REDLITHIUM[™] XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

