



# Garage Door Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 01/06/2016

Revision date: 12/02/2016

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Garage Door Lubricant  
Product code : 16-GDL, 20-GDL, GDL-TS

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Multi-Purpose Lubricant.

#### 1.3. Details of the supplier of the safety data sheet

The Blaster Corporation  
8500 Sweet Valley Drive  
Valley View, Ohio 44125 - USA  
T (216) 901-5800 - F (216) 901-5801  
[www.blastercorp.com](http://www.blastercorp.com)

#### 1.4. Emergency telephone number

Emergency number : ChemTel 800-255-3924

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification


Flammable Aerosol 2  
Gases Under Pressure - Dissolved gas  
Serious Eye Damage 1  
Aspiration Toxicity 1

#### 2.2. Label elements

##### GHS-US labelling

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye damage. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear eye protection/face protection. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable.

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	30 - 60	Flam. Liq. 3 Asp. Tox. 1

# Garage Door Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Name	Product identifier	%	GHS-US classification
Naphtha, petroleum, heavyalkylate	(CAS No) 64741-65-7	15 - 40	Flam. Liq. 3 Asp. Tox. 1
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zincsalts	(CAS No) 68649-42-3	1 - 5	Skin Irrit. 2 Eye Dam. 1
Carbon dioxide	(CAS No) 124-38-9	1 - 5	Compressed gas

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical, carbon dioxide, halons, foam.
- Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon, hydrocarbons.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.2. Methods and material for containment and cleaning up

- For containment : Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Provide ventilation.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

# Garage Door Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Pressurized container: Do not pierce or burn, even after use.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep dry.

#### 7.3. Specific end use(s)

Not available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)		
USA ACGIH	ACGIH TWA	Not available.
USA OSHA	OSHA PEL (TWA)	Not available.
Naphtha, petroleum, heavy alkylate (64741-65-7)		
USA ACGIH	ACGIH TWA	100 ppm
USA OSHA	OSHA PEL (TWA)	100 ppm
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts (68649-42-3)		
USA ACGIH	ACGIH TWA	Not available.
USA OSHA	OSHA PEL (TWA)	Not available.
Carbon dioxide (124-38-9)		
USA ACGIH	ACGIH TWA (ppm)	5000 ppm
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	9000 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

#### 8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls : Maintain levels below Community environmental protection thresholds.
- Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Gas/Pressurized Liquid.
- Appearance : Clear.
- Color : Colorless.
- Odor : Mild aliphatic.
- Odor threshold : No data available.
- pH : No data available.

# Garage Door Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Relative evaporation rate (butylacetate=1)	: > 1
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: 182 °C (360 °F)
Flash point	: 54 °C (130 °F) [TCC]
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapor pressure	: No data available.
Relative vapor density at 20 °C	: No data available.
Relative density	: 0.81
Solubility	: Negligible.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

Flame projection length	: 0 cm
Heat of combustion	: 46.6 kJ/g

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Excessive water.

### 10.5. Incompatible materials

Strong oxidizing agents, strong reducing agents.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon, hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

Garage Door Spray Lubricant	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5 mg/l/4h
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Naphtha, petroleum, heavy alkylate (64741-65-7)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

# Garage Door Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### Naphtha, petroleum, heavy alkylate(64741-65-7)

LC50 inhalation rat	> 5.04 mg/l/4h
---------------------	----------------

Skin corrosion/irritation : Based on available data, the classification criteria are not met.  
Serious eye damage/irritation : Causes serious eye damage.  
Respiratory or skin sensitization : Based on available data, the classification criteria are not met.  
Germ cell mutagenicity : Based on available data, the classification criteria are not met.  
Carcinogenicity : Based on available data, the classification criteria are not met.  
Reproductive toxicity : Based on available data, the classification criteria are not met.  
Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.  
Specific target organ toxicity (repeated exposure) : Based on available data, the classification criteria are not met.  
Aspiration hazard : May be fatal if swallowed and enters airways.  
  
Symptoms/injuries after inhalation : May cause respiratory tract irritation.  
Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.  
Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.  
  
Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

### 12.2. Persistence and degradability

#### Garage Door Spray Lubricant

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### Garage Door Spray Lubricant

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available.

### 12.5. Other adverse effects

Effect on ozone layer : No additional information available.

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapors may accumulate in the container. Do not incinerate empty containers.

## SECTION 14: Transport information

In accordance with DOT

### 14.1. UN number


UN-No.(DOT) UN1950

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : AEROSOLS, flammable, limited quantities

Department of Transportation (DOT) Hazard Classes : 2.1

Hazard labels (DOT) :



# Garage Door Lubricant

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### 14.3. Additional information

Other information : No supplementary information available.  
Special transport precautions : Do not handle until all safety precautions have been read and understood.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

### 15.2. US State regulations

#### Garage Door Spray Lubricant

State or local regulations	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	--

## SECTION 16: Other information

Date of issue : 01/06/2016  
Revision date : 12/02/2016  
Other information : None.

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*