



Silicone Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 10/25/2016

Revision date: 11/30/2016

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : Silicone Lubricant
Product code : 8-SL-S, 16-SL , 20-SL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Multi-Purpose Lubricant

1.3. Details of the supplier of the safety data sheet

The Blaster Corporation
8500 Sweet Valley Drive
Valley View, Ohio 44125 - USA
T (216) 901-5800 - F (216) 901-5801
www.blastercorp.com

1.4. Emergency telephone number

Emergency number : ChemTel 800-255-3924 Contract #: MIS7234544

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1
Dissolved gas
STOT SE 3
Asp. Tox. 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS04

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely Flammable aerosol. Contains gas under pressure; may explode if heated. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents/container in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Silicone Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

3.2. Mixtures

Name	Product identifier	%
Alkanes, C9-11-iso-	(CAS No) 68551-16-6	50 - 60
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	30 - 40
Carbon dioxide	(CAS No) 124-38-9	1 - 4

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide, dry chemical, halons or foam.
- Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon and oxides of nitrogen.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

Silicone Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

6.3. Methods and material for containment and cleaning up

- For containment : Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapor or spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep in fireproof place.
- Incompatible materials : Heat sources. Direct sunlight.
- Storage area : Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)

Not applicable

Alkanes, C9-11-iso- (68551-16-6)

Not applicable

Carbon dioxide (124-38-9)

ACGIH	ACGIH TWA (ppm)	5000 ppm
ACGIH	ACGIH STEL (ppm)	30000 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

8.2. Exposure controls

- Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
- Hand protection : Wear chemically resistant protective gloves.
- Eye protection : Safety glasses or goggles are recommended when using product.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Environmental exposure controls : Maintain levels below Community environmental protection thresholds.
- Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Gas/Pressurized Liquid.
- Appearance : Clear
- Colour : Colourless
- Odour : Mild aliphatic

Silicone Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 360 °F / 182 C
Flash point	: 130 °F / 54 C (TCC)
Relative evaporation rate (butylacetate=1)	: > 1 (NBA = 1)
Flammability (solid, gas)	: Flammable aerosol
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.81 (water = 1)
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

Heat of Combustion	: 43.5 kJ/g
Flame Projection	: 0 inches
Flashback	: None

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Extremely flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sparks. Open flame. Direct sunlight.

10.5. Incompatible materials

Strong oxidizers. Strong reducing agents. Water.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon and oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified.

Silicone Lubricant	
LD50 oral rat	> 2000 mg/kg (Calculated Acute Toxicity Estimate)
LD50 dermal rabbit	> 2000 mg/kg (Calculated Acute Toxicity Estimate)
LC50 inhalation rat	> 5 mg/l/4h (Calculated Acute Toxicity Estimate)
Alkanes, C9-11-iso- (68551-16-6)	
LD50 oral rat	34600 mg/kg
LD50 dermal rat	15400 mg/kg
ATE US (oral)	34600.000 mg/kg bodyweight
ATE US (dermal)	15400.000 mg/kg bodyweight

Silicone Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

12.2. Persistence and degradability

Silicone Lubricant	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Silicone Lubricant	
Bioaccumulative potential	Not established.

Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159

Carbon dioxide (124-38-9)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container.

Silicone Lubricant

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Carbon dioxide (124-38-9)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Date of issue : 10/25/2016

Revision date : 11/30/2016

Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.