


DIE GRINDERS

Viking has more models to allow you to own the right tool for the right job at the most cost effective price.

Straight / Angle Superior Performance in a Variety of Applications / Many Sizes to Meet Any Need / Variable Speed Operation with Safety Throttle Lever / 4 CFM / 1/4 NPT Air Inlet / 3/8" Minimum Hose Size / 90-100 PSI Maximum Pressure



V324 1/4" Collet, Heavy-Duty, Straight

V362 1/4" Collet, Mini, Angle

Model	RPM	Type	HP	Collet/Chuck	Noise	Vibration	Exhaust	Length	Weight
V361	22,000	Straight	0.4	1/4"	86 dB	2.5 M/S2	Front	6-1/4"	1-3/4 Lbs.
V361DC	22,000	Straight	0.4	3/8" Ch.	86 dB	2.5 M/S2	Front	6-1/4"	1-3/4 Lbs.
V362	20,000	Angle	0.4	1/4"	86 dB	2.5 M/S2	Front	6"	1 Lbs.
V363	22,000	Straight	0.4	1/4"	86 dB	2.5 M/S2	Front	6-7/8"	1 Lbs.
V363DC	22,000	Straight	0.4	3/8" Ch.	86 dB	2.5 M/S2	Rear	6-7/8"	1 Lbs.
V364	15,000	Angle	0.4	1/4"	86 dB	2.5 M/S2	Rear	6-3/4"	1-1/3 Lbs.
V323	20,000	Straight	0.5	3/8" Ch.	82 dB	2.5 M/S2	Rear	7-1/4"	1-1/4 Lbs.
V324	20,000	Straight	0.5	1/4"	82 dB	<2.5 M/S2	Rear	7-3/8"	1-1/4 Lbs.

Straight / Angle: Value Superior Performance in a Variety of Applications / Many Sizes to Meet Any Need / 1/4 NPT Air Inlet / 3/8" Minimum Hose Size / 90 PSI Maximum Pressure / Rear Exhaust (Except VT3003A) / 1 Year Warranty



VT3000 1/4" Collet, Lightweight, Straight

VT3001A Gearless 105° Angle

Model	RPM	Type	CFM	HP	Collet	Noise	Vibration	Length	Weight
VT3000	Straight	25,000	14	0.3	1/4"	93 dB	5.4 M/S2	6-5/16"	1.1 Lbs.
VT3000A	Angle	20,000	14	0.3	1/4"	93 dB	5.4 M/S2	6-5/16"	1.65 Lbs.
VT3001	Straight	22,000	4	0.3	1/4"	93 dB	5.4 M/S2	6-3/4"	1.6 Lbs.
VT3001A	105° Angle	25,000	4	0.3	1/4"	83 dB	2.0 M/S2	6-1/8"	1.6 Lbs.
VT3003A	Angle	20,000	12	0.3	1/4"	86 dB	3 M/S2	5"	1.2 Lbs.
VT3005	Straight	22,000	4	0.3	1/4"	93 dB	5.4 M/S2	7"	1.65 Lbs.

Micro Twist Throttle with Variable Speed Control / Cylinder is Made of Special Heat Treated Alloy Steel / Internal Surfaces Precision Ground / Heavy-Duty High Speed Bearings / Includes 52" Air Hose & Fittings / 1/4 NPT Air Inlet / 3/8" Minimum Hose Size / 90 PSI Maximum Pressure



VT3400 High Speed Micro

Model	RPM	CFM	HP	Collet	Noise	Vibration	Length	Weight	Warranty
VT3400	60,000	2.25	1	1/8"	81 dB	4 M/S2	6"	0.8 Lbs.	1 yr.

Extended Industrial Duty / Precision Machined & Hardened Steel Gears / Air Motor with Exceptionally High Turning Force / High Quality Ball Bearings / Safety Throttle Lever / Ergonomic Square Handle / Rear Exhaust / 3/8" Minimum Hose Size / 90 PSI Maximum Pressure



VT3002E Extended

Model	RPM	CFM	HP	Collet	Noise	Air Inlet	Vibration	Length	Weight	Warranty
VT3002E	22,000	4	0.3	1/4"	93 dB	1/4"	5.4 M/S2	13"	2.8 Lbs.	1 yr.
VT3004E	4,500	4	0.3	1/4"	80 dB	1/4"	5.4 M/S2	8"	2.31 Lbs.	yr.
VT3009E	22,000	4	0.6	1/4"	93 dB	1/4"	5.4 M/S2	13"	2.68 Lbs.	1 yr.
VT3010E	25,000	3.5	0.6	1/4"	93 dB	1/4"	5.4 M/S2	10-1/4"	1.41 Lbs.	1 yr.

Pneumatic Oil

V509 1 oz. / V512 4 oz. / V511 32 oz.



- Specially formulated for pneumatic tools, in-line oilers & lubricators
- High and low temperature resistant
- Prevents rusting by throwing off moisture when present
- Virtually eliminates lubrication blow-out due to air pressure
- Provides positive lubrication for smooth starting and longer life
- Will not harm O-rings and seals
- Aids in dissolving gums & sludges that cut down tool speed & reduce power output
- Case of 12

GRINDERS

Viking offers a great selection of industrial duty grinders to choose from. Designed to handle increased precision and production efficiently & easily.

Standard-Duty Precision Air Motor With Exceptionally High Turning Force / Sealed Ball Bearing Motor / Compact Body / Front Exhaust / Safety Locking Lever With Variable Throttle / Removable Side Handle / Includes Guard, Hex Wrenches & Spanner / Wheels Not Included / 100 PSI Maximum Pressure / 1 M/S2 Vibration / 1 Year Warranty



VT3104 4"



VT3105 4.5"/5"

Model	RPM	CFM	HP	Wheel	Noise	Air Inlet	Min. Hose	Arbor	Length	Weight
VT3104	11,000	6	0.75	4"	95 dB	1/4"	3/8"	3/8-24"	9"	4 Lbs.
VT3105	11,000	6	0.75	4.5"/5"	94 dB	1/4"	3/8"	5/8-11"	9"	4.6 Lbs.
VT3107	7,000	9	1	7"	96 dB	3/8"	1/2"	5/8-11"	13-1/2"	6.6 Lbs.

Heavy-Duty Cast Construction / Speed Regulating Valve / Vibration-Dampening Side Handle / Lock Off Safety Lever / Controlled Variable Throttle Lever / Adjustable Exhaust Direction / Wheels Not Included / 90 PSI Maximum Pressure / 0.6 M/S2 Vibration / 1 Year Warranty



VT3205 4.5"/5"



VT3207 7"

Model	RPM	CFM	HP	Wheel	Noise	Air Inlet	Min. Hose	Arbor	Length	Weight
VT3204	13,600	34	0.9	4"	95 dB	1/4"	3/8"	3/8-24"	9-11/16"	4.6 Lbs.
VT3205	10,900	34	0.9	4.5"/5"	94 dB	1/4"	3/8"	5/8-11"	9-11/16"	4.9 Lbs.
VT3207	7,600	57	1.2	7"	96 dB	3/8"	1/2"	5/8-11"	11-13/16"	8.8 Lbs.

Vertical, Heavy-Duty Side Exhaust / Safety Throttle Trigger / Hardened Steel Motor Parts / Over Speed Auto Shut-Off / High Force Corrosion-Resistant Governor, Unitized Motor Design With Hardened Steel End Plates & Liner To Maintain Constant Speed Under Load / Can Be Fitted With Grinding Wheels & Wire Brushes / Wheels Not Included / 90 PSI Maximum Pressure / 1/2" Min. Hose Size / 1 Year Warranty



VT3507 7"

Model	RPM	CFM	HP	Wheel	Noise	Air Inlet	Arbor	Vibration	Length	Weight
VT3507	7,000	36	2.5	7"	96 dB	1/2"	5/8-11"	3.6 M/S2	7-1/4"	10.5 Lbs.
VT3509	6,000	36	3	9"	95 dB	1/2"	5/8-11"	4.1 M/S2	7-1/2"	12.75 Lbs.

DRILLS

Our exceptional engineering & construction provide innovative designs with a focus on ergonomics have resulted in drills that are light weight, balanced and powerful.

Pistol Grip, Straight & Angle One Hand Quick Reverse Lever (on reversible drills) / Elastomer Handle Grip (Pistol) / Heavy Duty Ball & Needle Bearing Construction / Planetary Gear Reduction Balances Drilling Load & Maximizes Performance / Precision Air Motor with Exceptionally High Turning Force / 3/8" Min. Hose Size / 90 PSI Maximum Pressure / 1 Year Warranty



VT5000 3/8" Reversible, Pistol Grip



VT5006 1/2", Pistol Grip



VT5003 3/8" Straight



VVO408 3/8" Reversible Angle

Model	Type	RPM	CFM	HP	Chuck Cap	Noise	Air Inlet	Vibration	Length	Weight
VT5000	Pistol	1,800	4	.33	3/8"	85 dB	1/4"	<2.5 M/S2	7"	2.4 Lbs.
VT5001	Pistol	2,600	4	.33	3/8"	90 dB	1/4"	<2.5 M/S2	7-3/4"	2.4 Lbs.
VT5006	Pistol	500	4	.50	1/2"	89 dB	1/4"	<2.5 M/S2	9-1/2"	4 Lbs.
VT5007	Pistol	800	4	.50	1/2"	89 dB	1/4"	<2.5 M/S2	7-1/2"	4 Lbs.
VT5002	Straight	2,600	4	.33	3/8"	90 dB	1/4"	<2.5 M/S2	8-1/2"	2 Lbs.
VT5003	Straight	4,500	4	.33	3/8"	90 dB	1/4"	<2.5 M/S2	8-3/4"	2.4 Lbs.
VVO408	Angle	1,500	4	.33	3/8"	94 dB	1/4"	<2.6 M/S2	7"	2.4 Lbs.
VT5005A	Angle	1,900	4	.33	3/8"	92 dB	1/4"	<2.6 M/S2	8"	2.4 Lbs.