

629

Super Thin Adjustable Wrench

Specifications: *Jaw and handle thickness: .25" Jaw A Opens: 9/16 to 1-9/16 Jaw B Opens: 1-1/16 to 2-1/16 Length: 9"*

Comes with two Quick-Change Jaws. Made of super strong Drop Forged Alloy Steel Pull back on screw to switch or adjust in less than a second!



**manufacturer's suggested list:
\$60.00**

3202

2pc Disconnect Tool for Fuel and A/C lines,

- Strong, light and durable aluminum construction.
- Simple push-on and pull-off action.
- Thin lips slide under tight hose quickly.
- 6 popular sizes cover most cars.
- Color keyed for easy identification.
- Durable and soft powder coating will not scratch tubing.

sizes: (5/16", 3/8")



3262

2pc Offset Disconnect Tool,

Patent#(US6195862B1)

The 2 most popular sizes for fuel lines.

sizes: (5/16", 3/8")



V8 1008

8pc Pull Rod Kit (body work)

Introducing our new 8pc Pull Rod Kit:

- ◆ An economical and efficient tool to fix dents on car bodies.
- ◆ Just drill, pull, fill, sand and paint from outside the car body
- ◆ Hooks are made of rust resistant alloy steel.
- ◆ Heat treated for strength.
- ◆ Drill bits are not under warranty.

