ATAK LIGHTING

PRO-FOCUS™ FLASHLIGHTS

- Adjustable beam goes from spot to flood.
- Aluminum housing.
- Water and impact resistant.



| | | | | | | | Run | Beam | Bat | ttery | | Head |
|--------------|--------|----|----|-----|---------|--------|------|----------|------|-------|--------|----------|
| Item # | | IP | MP | PKG | Display | Lumens | Time | Distance | Qty. | Туре | Length | Diameter |
| 535 * | 2 Pack | 4 | 16 | CRD | Ν | 340 | 1 | 200m | 4 | AAA | 5.125" | 1.5" |
| 538 * | 2 Pack | 4 | 16 | DBL | Y | 500 | 3.5 | 172m | 3 | С | 8.625" | 1.75" |
| 540 * | 2 Pack | 4 | 16 | DBL | Ν | 500 | 3.5 | 172m | 3 | С | 8.625" | 1.75" |
| 541 * | | 6 | 24 | DBL | Y | 1000 | 6 | 203m | 9 | AA | 9" | 2" |
| 549 * | XL | 6 | 24 | DBL | Y | 1500 | 5 | 201m | 9 | AA | 12.5" | 2" |

FLASHLIGHTS WITH COB TECH

 Includes new chip on board (COB) technology that Includes red provides a higher lumen output and longer life. safety flasher

541

- Durable aluminum housing.
- Water and impact resistant.



ATAK°

606

546

ATAK



ATAK[®]

| | | | | | | Run | Beam | Battery | | Head | |
|----------------|-------------------------|----|----|-----|--------|------|----------|---------|------|---------|----------|
| Item # | | IP | MP | PKG | Lumens | Time | Distance | Qty. | Туре | Length | Diameter |
| 546* W | V/ Slide COB Work Light | 6 | 24 | DBL | 1000 | 6 | 201m | 9 | AA | 11.375" | 2" |
| 615* W | V/ COB Work Light | 6 | 36 | DBL | 250 | 3 | 188m | 4 | AAA | 7.625" | 1.5" |
| 606 * C | COB Pen Light | 6 | 48 | CRD | 200 | 1.5 | 100 | 2 | AA | 6.75" | 1" |

LED TIRE THUMPER

- Adjustable beam goes from spot to flood.
- Anodized aluminum housing.
- Water and impact resistant.

| A second second | ATAK | |
|-----------------|------|--|
| | | |
| | | |

ATAK

| | | | | | Run | Beam | B | attery | | Head |
|--------|----|----|-----|--------|------|----------|------|--------|--------|----------|
| Item # | IP | MP | PKG | Lumens | Time | Distance | Qty. | Туре | Length | Diameter |
| 204* | 6 | 24 | DBL | 200 | 17 | 220m | 4 | AA | 16" | 1.25" |

/ULIVI FENLI

- Uses professional grade lifetime SMD.
- Aerospace anodized aluminum housing.
- Water resistant

| • water n | 251510 | i ii. | | | Run | Beam | В | attery | | Head | |
|--------------|--------|-------|-----|--------|------|----------|------|--------|--------|----------|--|
| Item # | IP | MP | PKG | Lumens | Time | Distance | Qty. | Туре | Length | Diameter | |
| 626 * | 6 | 24 | DBL | 70 | 6.5 | 98ft | 2 | AAA | 5" | 0.5" | |



BLK: Bulk | CAS: Storage Case | CBX: Color Box | CRD: Carded | CLM: Clamshell | DBL: Double Blister LAB: Color Label | RAC: Storage Rack | SHK: Shrink Wrap | SLV: Sleeve | TAB: Hang Tab | WBX: White Box