

1. Identification

Product identifier	LPS® Max 2
Other means of identification	
Part Number	90216
Recommended use	An industrial lubricant designed to displace moisture from equipment, provide heavy-duty lubrication and rust prevention.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer	
Company name	ITW Pro Brands
Address	4647 Hugh Howell Rd. Tucker, GA 30084
Country	(U.S.A.) Tel: +1 770-243-8800
In Case of Emergency	1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.)
Website	www.lpslabs.com
E-mail	lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.
Precautionary statement	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse.
Storage	Store locked up. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates Petroleum Hydrotreated Light		64742-47-8	70 - 80
Petroleum Oil		64742-52-5	10 - 20
Calcium alkylnaphthalenesulfonate		57855-77-3	1 - 5
Carbon Dioxide		124-38-9	1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash the skin immediately with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	If swallowed, seek medical advice immediately and show this container or label.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
--------------------------------------	--

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

U.S. - OSHA

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	PEL	5 mg/m3	Oil mist
Petroleum Oil (CAS 64742-52-5)	PEL	5 mg/m3	Oil mist
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m3	Oil mist.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
4-Methylpentan-2-one (CAS 108-10-1)	PEL	410 mg/m3
		100 ppm
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
Primary Amyl Acetate (CAS 628-63-7)	PEL	525 mg/m3
		100 ppm

ACGIH

Components	Type	Value	Form
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)	TWA	5 mg/m3	Oil mist
Petroleum Oil (CAS 64742-52-5)	TWA	5 mg/m3	Oil mist
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m3	Respirable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Methyl Butyl Acetate (CAS 624-41-9)	STEL	100 ppm
	TWA	50 ppm
4-Methylpentan-2-one (CAS 108-10-1)	STEL	75 ppm
	TWA	20 ppm
Acetophenone (CAS 98-86-2)	TWA	10 ppm
Benzyl Acetate (CAS 140-11-4)	TWA	10 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Primary Amyl Acetate (CAS 628-63-7)	STEL	100 ppm
	TWA	50 ppm

U.S. - NIOSH

Components	Type	Value	Form
White Mineral Oil (CAS 8042-47-5)	TWA	5 mg/m3	Mist.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
4-Methylpentan-2-one (CAS 108-10-1)	STEL	300 mg/m3	
		75 ppm	
	TWA	205 mg/m3	
Calcium Carbonate (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
Primary Amyl Acetate (CAS 628-63-7)	TWA	525 mg/m3	
		5000 ppm	
		100 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
Acetophenone (CAS 98-86-2)	TWA	50 mg/m3
		10 ppm
Benzaldehyde (CAS 100-52-7)	STEL	17.4 mg/m3
		4 ppm
	TWA	8.7 mg/m3
		2 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
4-Methylpentan-2-one (CAS 108-10-1)	1 mg/l	Methyl isobutyl ketone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.

Form Aerosol.

Color Brown.

Odor Slight petroleum odor. Cherry.

Odor threshold Not established

pH Not applicable

Melting point/freezing point < -58 °F (< -50 °C)

Initial boiling point and boiling range 383 °F (195 °C) @ 101 kPa

Flash point 174.2 °F (79.0 °C) Tag Closed Cup (dispensed liquid)

Evaporation rate < 0.1 BuAc

Flammability (solid, gas) Flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 0.6 %

Flammability limit - upper (%) 7 %

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure < 0.05 mm Hg @ 20°C (dispensed liquid)

Vapor density 4.7 (air = 1)

Relative density Not available.

Solubility(ies)

Solubility (water) < 3 %

Partition coefficient (n-octanol/water) < 1

Auto-ignition temperature > 442.4 °F (> 228 °C)

Decomposition temperature Not established

Viscosity < 7 cSt

Viscosity temperature 77 °F (25 °C)

Other information

Explosive properties Not explosive.

Heat of combustion > 30 kJ/g

Oxidizing properties Not oxidizing.

Percent volatile 92 - 95 %

Specific gravity 0.82 - 0.86 @ 20°C

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur.

Conditions to avoid Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components	Species	Test Results
4-Methylpentan-2-one (CAS 108-10-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 16000 mg/kg
Inhalation		
LC50	Rat	8.2 mg/l, 4 Hours
Acetophenone (CAS 98-86-2)		
<u>Acute</u>		
Dermal		
LD50	Rat	3300 mg/kg, 24 Hours
Oral		
LD50	Rat	0.81 g/kg
Benzaldehyde (CAS 100-52-7)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 2000 mg/kg
Oral		
LD50	Rat	1300 mg/kg
Benzyl Acetate (CAS 140-11-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5 g/kg
Oral		
LD50	Rat	> 2000 mg/kg
Calcium Carbonate (CAS 471-34-1)		
<u>Acute</u>		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 0.1 mg/l, 8 Hours
Oral		
LD50	Rat	> 5000 mg/kg

Components	Species	Test Results
Petroleum Oil (CAS 64742-52-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 3.9 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
White Mineral Oil (CAS 8042-47-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	2.2 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
ACGIH Carcinogens		
4-Methylpentan-2-one (CAS 108-10-1)	A3 Confirmed animal carcinogen with unknown relevance to humans.	
Benzyl Acetate (CAS 140-11-4)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
4-Methylpentan-2-one (CAS 108-10-1)	2B Possibly carcinogenic to humans.	
Benzyl Acetate (CAS 140-11-4)	3 Not classifiable as to carcinogenicity to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Not listed.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	May be fatal if swallowed and enters airways.	
Chronic effects	Prolonged inhalation may be harmful.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
4-Methylpentan-2-one (CAS 108-10-1)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 492 - 593 mg/l, 96 hours

Components	Species	Test Results
Acetophenone (CAS 98-86-2)		
Aquatic		
<i>Acute</i>		
Fish LC50	Fathead minnow (<i>Pimephales promelas</i>)	155 mg/l, 96 hours
Benzaldehyde (CAS 100-52-7)		
Aquatic		
<i>Acute</i>		
Fish LC50	Bluegill (<i>Lepomis macrochirus</i>)	0.8 - 1.44 mg/l, 96 hours
Benzyl Acetate (CAS 140-11-4)		
Aquatic		
<i>Acute</i>		
Fish LC50	Medaka, high-eyes (<i>Oryzias latipes</i>)	3.48 - 4.6 mg/l, 96 hours
Calcium Carbonate (CAS 471-34-1)		
Aquatic		
<i>Acute</i>		
Fish LC50	Western mosquitofish (<i>Gambusia affinis</i>)	> 56000 mg/l, 96 hours
Distillates Petroleum Hydrotreated Light (CAS 64742-47-8)		
Aquatic		
<i>Acute</i>		
Fish LC50	Bluegill (<i>Lepomis macrochirus</i>)	2.2 mg/l, 4 days
Primary Amyl Acetate (CAS 628-63-7)		
Aquatic		
<i>Acute</i>		
Fish LC50	Western mosquitofish (<i>Gambusia affinis</i>)	65 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

LPS® Max 2	< 1
4-Methylpentan-2-one	1.31
Acetophenone	1.58
Benzaldehyde	1.48
Benzyl Acetate	1.96
Primary Amyl Acetate	2.3

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
D001: Waste Flammable material with a flash point <140 F
D003: Waste Reactive material

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not available.
Environmental hazards
Marine pollutant No
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950
UN proper shipping name Aerosols, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not available.
Environmental hazards No.
ERG Code 10L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information
Passenger and cargo aircraft Allowed with restrictions.
Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950
UN proper shipping name AEROSOLS, flammable
Transport hazard class(es)
Class 2.1
Subsidiary risk -
Label(s) 2.1
Packing group Not available.
Environmental hazards
Marine pollutant No
EmS Not available.
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



**General information**

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

4-Methylpentan-2-one (CAS 108-10-1)	Listed.
Acetophenone (CAS 98-86-2)	Listed.
Primary Amyl Acetate (CAS 628-63-7)	Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories	Flammable (gases, aerosols, liquids, or solids) Gas under pressure Aspiration hazard
-------------------------------------	--

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
METHYL ISOBUTYL KETONE	108-10-1	< 0.1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

4-Methylpentan-2-one (CAS 108-10-1)
Acetophenone (CAS 98-86-2)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

4-Methylpentan-2-one (CAS 108-10-1)	6715
-------------------------------------	------

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Benzaldehyde (CAS 100-52-7)	50 %WV
4-Methylpentan-2-one (CAS 108-10-1)	35 %WV

DEA Exempt Chemical Mixtures Code Number

4-Methylpentan-2-one (CAS 108-10-1)	6715
Benzaldehyde (CAS 100-52-7)	8256

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

4-Methylpentan-2-one (CAS 108-10-1)	Low priority
Benzaldehyde (CAS 100-52-7)	High priority

US state regulations**US. New Jersey Worker and Community Right-to-Know Act**

4-Methylpentan-2-one (CAS 108-10-1)
 Acetophenone (CAS 98-86-2)
 Benzaldehyde (CAS 100-52-7)
 Benzyl Acetate (CAS 140-11-4)
 Carbon Dioxide (CAS 124-38-9)
 Primary Amyl Acetate (CAS 628-63-7)

California Proposition 65

WARNING: This product can expose you to 4-Methylpentan-2-one, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

4-Methylpentan-2-one (CAS 108-10-1)	Listed: November 4, 2011
-------------------------------------	--------------------------

California Proposition 65 - CRT: Listed date/Developmental toxin

4-Methylpentan-2-one (CAS 108-10-1)	Listed: March 28, 2014
-------------------------------------	------------------------

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

4-Methylpentan-2-one (CAS 108-10-1)
 Acetophenone (CAS 98-86-2)
 Petroleum Oil (CAS 64742-52-5)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-15-2021
Version #	01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.