

KEY FEATURES

- Program power: 300 W
- Sensitivity: 92 dB (1W / 1m)
- FEA optimized ferrite magnetic circuit
- Weatherproof paper cone and Santoprene™ surround
- Shorting cap for extended response and low harmonic distortion
- Extended controlled displacement: $X_{max} \pm 5,7$ mm
- 16 mm peak-to-peak excursion before damage



TECHNICAL SPECIFICATIONS

Nominal diameter	125 mm	5 in
Rated impedance	8 Ω	
Minimum impedance	6,7 Ω	
Power capacity*	150 W _{AES}	
Program power	300 W	
Sensitivity	92 dB	1W / 1m @ Z _N
Frequency range		70 - 10.000 Hz
Recom. enclosure. vol.	4 / 10 l	0,14 / 0,35 ft ³
Voice coil diameter	38,1 mm	1,5 in
BL factor		8,5 N/A
Moving mass		0,010 kg
Voice coil length		14 mm
Air gap height		6 mm
X _{damage} (peak to peak)		16 mm

Notes:


* The power capacity is determined according to AES2-1984 (r2003) standard. Program power is defined as the transducer's ability to handle normal music program material.

** T-S parameters are measured after an exercise period using a preconditioning power test. The measurements are carried out with a velocity-current laser transducer and will reflect the long term parameters (once the loudspeaker has been working for a short period of time).

*** The X_{max} is calculated as $(L_{vc} - H_{ag})^2 + (H_{ag}/3,5)$, where L_{vc} is the voice coil length and H_{ag} is the air gap height.

THIELE-SMALL PARAMETERS**

Resonant frequency, f _s	72 Hz
D.C. Voice coil resistance, R _e	5,2 Ω
Mechanical Quality Factor, Q _{ms}	7,5
Electrical Quality Factor, Q _{es}	0,35
Total Quality Factor, Q _{ts}	0,33
Equivalent Air Volume to C _{ms} , V _{as}	5,7 l
Mechanical Compliance, C _{ms}	451 μm / N
Mechanical Resistance, R _{ms}	0,65 kg / s
Efficiency, η ₀	0,6 %
Effective Surface Area, S _d	0,0095 m ²
Maximum Displacement, X _{max} ***	5,7 mm
Displacement Volume, V _d	49 cm ³
Voice Coil Inductance, L _e @ 1 kHz	0,6 mH



Note: On axis frequency response measured with loudspeaker standing on infinite baffle in anechoic chamber, 1W @ 1m

MOUNTING INFORMATION

Overall diameter	155 mm	6,1 in
Bolt circle diameter	141,5 mm	5,6 in
Baffle cutout diameter:		
- Front mount	120 mm	4,7 in
Depth	80 mm	3,1 in
Volume displaced by driver	0,5 l	0,02 ft ³
Net weight	2,2 kg	4,8 lb
Shipping weight	2,3 kg	5,1 lb

DIMENSION DRAWING

