

DeoxIT® Brand Rosin Soldering Flux

For electrical and electronic soldering applications

Part No.:	RSF-R80		
Formulation:	50-60%	WW Gum Rosin	
	15-25%	Dymerex Rosin	
	15-25%	Diethylene Glycol Dibutyl Ether	
Container Size:	RSF-R80-8G	syringe	8 g
	RSF-R80-2	jar	56 g
	RSF-R80-8	jar	226 g
	RSF-R80-40	pail	18.1 Kg



Description

RSF Rosin Flux is a mildly-activated rosin flux that is considerably more active than water-white rosin. Although its activity closely approaches that of fully activated rosins, it still conforms to all of the requirements of Type RMA (Rosin Core, Mildly Activated) of Federal Specification QQ-S-571. The RSF paste flux meets DOD-STD-2000 & also the IPC-J-004 standard for type ROL0, the lowest residue corrosivity category. Thermal stability enabling excellent wetting and reduced carbonization at soldering temperatures. RSF-R80 Rosin Flux is MADE IN USA.

Application

The active ingredients in RSF-R80 are non-ionic and non-conductive even in the presence of moisture. Like rosin, it becomes active only at elevated temperatures, reverting to an inactive state at room temperature. It is recommended for all applications where post-soldering cleaning is not feasible, and the residue must be highly insulating.

Physical Properties

Softening Point	160°F (71°C)
Rosin Grade	WW per Fed. Spec. LLL-R-626
Acid No. (of Rosin)	150
Water Extract Resistivity	110,000 ohm-cm
Effect on Copper Mirror	None
Fungus Resistance	Per MIL-E-5272
Nonflammable, noncorrosive.	



Residue Removal

In applications requiring cleaning, RSF-R80 flux residues can be readily removed using an aqueous saponifier cleaning process. Can be removed by wiping with a cloth or with cleaning solvent (Radio Shack® Precision Electronic Cleaner #64-4345 or DeoxIT® Flux WASH #DFW-V710).

Availability

RSF-R80 is available in standard 2 ounce (26 gms), 8 ounce (226 gms) and bulk drums

Safety

RSF-R80 is not considered toxic; however, its use in typical soldering processes will generate a small amount of decomposition and reaction product fumes. These fumes must be adequately exhausted for operator safety and comfort.

Shipping Information:

Hazardous: NO, Not regulated

Other Information:

RoHS Compliant: YES

MSDS (Material Safety Data) Link: <http://store.caig.com/s.nl/sc.18/category.233/.f>

Search MSDS by Part No. or Category - MSDS Number is RSF-R80.

Product Sheet: <http://store.caig.com/s.nl/sc.2/category.2341/.f>

MANUFACTURER DISCLAIMER:

To the best of our knowledge, the information contained herein is accurate. However, neither CAIG Laboratories, Inc., or any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. All materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. All service performed on internal parts and equipment should be provided by qualified technicians.

Contact Information:



North America

CAIG Laboratories, Inc.
12200 Thatcher Court
Poway, CA 92064 USA
Tel: (858) 486-8388
Fax: (858) 486-8398

Website: www.caig.com
www.deoxit.com

General Email: info@caig.com

Technical Email: tech@caig.com