



Avanté® ANSI •



VENTED
FRAME



RUBBER
NOSEPIECE

Vented frame // Flexible temples //
Built-in rubber nosepiece // Custom
imprinting available

Black Frame | 7 Variations

- SB4510D • Clear
- SB4520D • Gray
- SB4530D • Amber
- SB4560D • Infinity Blue
- SB4570D • Silver Mirror
- SB4575D • Blue Mirror
- SB4580D • I/O Mirror



Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB4510D	P + U6	P Z87 +	Weight: 26.9 gm	Lens: polycarbonate
SB4520D	P + S	P Z87 +	PD: 64 mm	Frame: polycarbonate
SB4530D	P + S	P Z87 +	Bridge: 14.27 mm	Temples: polycarbonate
SB4560D	P + S	P Z87 +	Lens base: 8 curve	Temple Tips: rubber
SB4570D	P + S	P Z87 +	Lens size diagonal: 76.48 mm	Screw: stainless steel
SB4575D	P + S	P Z87 +	Lens size vertical: 38.39 mm	Nosepiece: thermoplastic rubbers (TPR)
SB4580D	P + S	P Z87 +	Lens thickness: 2.4 mm	

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

Overall length (lens - tip): 177 mm
Overall width (hinge - hinge): 136.65 mm
Closest point between temple tips: 101.26 mm
Closest point between lens: 19.03 mm