

# Cappture™ Plus ANSI • CE • CSA •



DIELECTRIC



INCLUDES STRAP

Dielectric // Fits over most prescription glasses  
// Flexible rubber gasket // Temples extend from browbar to avoid interference with prescription frame's temples // Custom imprinting available

## Rubber Gasket with Temples | 2 Variations

- S9910STMRG ●●● Clear **H2MAX AF**
- S9920STMRG ●●● Gray **H2MAX AF**



WATCH THE  
**CAPPTURE PLUS**  
VIDEO



Part No.	Lens Marking	Temple Marking
S9910STMRG	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
S9920STMRG	P Z87 + U6 L2.5 X	P Z87 + / P c SEI Z94.3

General Specifications
Weight: 51.7 gm
Bridge: 23.1 mm
Lens base: 2.5 curve
Lens size diagonal: 145.7 mm
Lens size vertical: 51.5 mm
Lens thickness: 1.8 mm
Overall length: 160 mm
Overall width: 132.5 mm

Materials
Lens: polycarbonate
Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
Nosepiece: polycarbonate
Temple: polycarbonate
Hinge: nylon + polycarbonate

Lens Marking Symbols
P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
X: Tested Anti-fog
UV Filter Transmittance
U6: .01% max effective far UV • .1% max near UV
Visible Light Filters
L2.5: 29% max visible light

Temple Marking Symbols
P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI Z94.3: CAN/CSA standard for eye and face protection devices