

Conaire™ ANSI • CSA •



RUBBER
TIPS

Lightweight // Rubber temples // Integrated side shields provide additional protection // Custom imprinting available

Black Frame | 3 Variations

- SB10710D ●● Clear
- SB10720D ●● Gray
- SB10734D ●● UV400 Blue Block

i SB10734D offers high contrast, 100% UV protection with an anti-reflective coating.



Part No.	Lens Marking	Temple Marking	Measurements	Materials
SB10710D	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 26.8 gm	Lens: polycarbonate
SB10720D	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	PD: 64 mm	Side Shield: polycarbonate
SB10734D	P Z87 + U6	P Z87 + / P c SEI Z94.3	Bridge: 10.8 mm	Frame: transparent nylon
			Lens base: 6 curve	Temples: polycarbonate
			Lens size diagonal: 54.5 mm	Temple tips: thermoplastic rubber
			Lens size vertical: 39.5 mm	Screw: stainless steel
			Lens thickness: 2.3 mm	
			Overall length (lens - tip): 153 mm	
			Overall width (hinge - hinge): 129 mm	
			Closest point between temple tips: 90.5 mm	
			Closest point between lens: 17.5 mm	

Lens Marking Symbols	Temple Marking Symbols
P: Manufacturer's mark	P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices	Z87: ANSI standard for eye and face protection devices
+: High impact	+: High impact
UV Filter Transmittance	c SEI Z94.3: CAN/CSA standard for eye and face protection devices
U6: .01% max effective far UV • .1% max near UV	
Visible Light Filters	
L2.5: 29% max visible light	