

## Cortez® ANSI • CE •



Durable co-injected temples // Ribbed cushioned nosepiece // Custom imprinting available

### Black Temples | 4 Variations

- SB3610S ●● Clear
- SB3610ST ●● Clear **H2X AF**
- SB3620S ●● Gray
- SB3680S ●● I/O Mirror

### Orange Temples | 1 Variation

- S03610S ● Clear

### Navy Temples | 1 Variation

- SN3610S ● Clear



S036



SN36

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB3610S	P Z87 + U6	P Z87 +	Weight: 23 gm	Lens: polycarbonate
SB3610ST	P Z87 + U6	P Z87 +	PD: 68 mm	Temples: polycarbonate & thermoplastic elastomers (TPE)
SB3620S	P Z87 + U6 L2.5	P Z87 +	Bridge: 12 mm	Hinge: polycarbonate
SB3680S	P Z87 + U6 L1.7	P Z87 +	Lens base: 9.5 curve	Screw: stainless steel
S03610S	P Z87 + U6	P Z87 +	Lens size diagonal: 70 mm	Nosepiece: polycarbonate & polyvinyl chloride (PVC)
SN3610S	P Z87 + U6	P Z87 +	Lens size vertical: 43 mm	
			Lens thickness: 2.20 mm	
			Overall length (lens - tip): 157 mm	
			Overall width (hinge - hinge): 137 mm	
			Closest point between temple tips: 73 mm	
			Closest point between lens: 15.5 mm	

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light