




POLYURETHANE DIPPED



GL405C

Nylon | Polyurethane

ANSI/ISEA 105



EN388



ANSI/ISEA 105 – CUT A3 | ABRASION 4 | PUNCTURE 4
 EN388 – ABRASION 4 | CUT X | TEAR 4 | PUNCTURE 2 | CUT TDM-100 C

Polyurethane coating on the palm and fingers for good grip and precision handling // 13 gauge nylon liner is strong yet lightweight // Glove design offers excellent touch sensitivity and low particulate shed // Knit cuff creates a snug fit to keep out debris

Suggested Applications

Automotive // Cutting Applications // Glass Handling // Metal Work

Glove Breakdown

Type: Dipped Glove
Material: Polyurethane
Outer Liner: 13 Gauge Nylon
Cuff: Nylon

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov
 This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.



Packaging

	Outer Polybag	Case	Made in China
GL402C5	12 Pair	120 Pair	

Product markings may vary // Updated as of 08.23

Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.