




# NITRILE DIPPED



# GL614

Polyester | Nitrile | Smooth

ANSI/ISEA 105



EN388



4121X

ANSI/ISEA 105 – CUT A1 | ABRASION 6 | PUNCTURE 2  
 EN388 – ABRASION 4 | CUT 1 | TEAR 2 | PUNCTURE 1 | CUT TDM-100 X

Smooth nitrile coating on palm and fingers offers an excellent grip on dry or wet surfaces by channeling liquids away // 10 gauge polyester liner offers a balance between comfort, durability, and moisture resistance // Knit cuff creates a snug fit to keep out debris

### Suggested Applications

General Assembly // Inspection // Janitorial //  
 Landscaping // Manufacturing // Warehousing

### Glove Breakdown

Type: Dipped Glove
Material: Smooth Nitrile
Outer Liner: 13 Gauge Polyester
Cuff: Polyester + Latex Elastic

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

### Packaging

	Outer Polybag	Case
GL614	12 Pair	120 Pair
Made in China		

Product markings may vary // Updated as of 06.23



### Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.