



## Goliath® ANSI • CE • CSA •



CO-INJECTED  
TEMPLES



POLARIZED  
OPTION

Co-injected rubber  
temples // Custom  
imprinting available

### Black Frame | 6 Variations

- SB5610D ••• Clear
- SB5620D ••• Gray
- SB5620DT ••• Gray **H2X AF**
- SB5621D ••• **Polarized** Gray
- SB5665D ••• Ice Blue Mirror
- SB5670D ••• Silver Mirror

### White Frame | 3 Variations

- SW5620D ••• Gray
- SW5655D ••• Sky Red Mirror
- SW5665D ••• Ice Blue Mirror



SW56

Part No.	Lens Markings	Frame Markings
SB5610D	P + U6	P Z87 + / P c SEI Z94.3
SB5620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB5620DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB5621D	P + S	P Z87 + / P c SEI Z94.3
SB5645D	P + S	P Z87 + / P c SEI Z94.3
SB5665D	P + S	P Z87 + / P c SEI Z94.3
SB5670D	P + S	P Z87 + / P c SEI Z94.3
SW5620D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SW5655D	P + S	P Z87 + / P c SEI Z94.3
SW5665D	P + S	P Z87 + / P c SEI Z94.3

### General Specifications

Weight: 35 gm  
 PD: 68 mm  
 Bridge: 13.8 mm  
 Lens base: 8 curve  
 Lens size diagonal: 62.6 mm  
 Lens size vertical: 37.6 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 163.5 mm  
 Overall width (hinge - hinge): 131 mm  
 Closest point between temple tips: 96.5 mm  
 Closest point between lens: 18 mm

### Materials

Lens: polycarbonate  
 Temples: polycarbonate & thermoplastic rubbers  
 Hinge: polycarbonate  
 Screw: stainless steel  
 Side shields: polycarbonate

### Lens Marking Symbols

P: Manufacturer's mark

+: High impact

S: Special Purpose

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices