

**Onix®** ANSI • Ballistic •



Ratcheting co-injected temples // Adjustable rubber nosepiece  
 // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

**Black and Green Frame | 1 Variation**

● SGR4910ST ●●    Clear H2X AF



Part No.	Lens Marking	Temple Marking
SGR4910ST	P Z87 + U6	P Z87 +

**Lens Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

**UV Filter Transmittance**

U6: .01% max effective far UV • .1% max near UV

**Temple Marking Symbols**

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

**General Specifications**

Weight: 27 gm  
 Bridge: 15 mm  
 Lens base: 8 curve  
 Lens size diagonal: 141 mm  
 Lens size vertical: 45 mm  
 Lens thickness: 2.2 mm  
 Overall length (lens - tip): 161 mm  
 Overall width (hinge - hinge): 128mm  
 Closest point between temple tips: 68 mm

**Materials**

Lens: polycarbonate  
 Temples: polycarbonate  
 Hinge: polycarbonate  
 Nosepiece: polycarbonate | Nosepad: TPE  
 Screw: Stainless Steel  
 Ratchets: Nylon  
 Side Shields: polycarbonate