

Onix Plus ANSI • CE •



Co-injected temples // Adjustable rubber nosepiece
 // Unique 3-angle adjustable flip lens // Outer lens
 flips down for applications where IR lenses are needed
 // Custom imprinting available



Black Frame | 2 Variations

-  SB4950STP • • Clear with 5.0 IR **H2X** AF
-  SB4960STP • • Clear with 3.0 IR **H2X** AF

Part No.	Lens Marking	Temple Marking
SB8650SF	P + U6 / P+ W5	P Z87 +
SB8660SF	P + U6 / P+ W3	P Z87 +

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 W: Welding filter

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact

General Specifications

Weight: 27 gm
 PD: 68 mm
 Bridge: 15 mm
 Lens base: 8 curve
 Lens size diagonal: 141 mm
 Lens size vertical: 45 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 161 mm
 Overall width (hinge - hinge): 128 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate & nylon
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: polycarbonate & thermoplastic elastomers (TPE)
 Side shields: polycarbonate
 Ratchets: nylon