



## PMXTREME® ANSI CE



Built-in rubber nosepiece


Ventilated flexible temples with rubber temple tips

Includes black lanyard cord

Part No.	Black Frame with Cord	
ESB6310STP ●●	AF	Clear
ESB6320STP ●●	AF	Gray



## PMXTREME® LED ANSI CE



Super bright swiveling LED bulbs (three lumens per side) allows you to see in dark places while keeping your hands free

Built-in rubber nosepiece and rubber temples tips

The alkaline batteries provide up to 50 hours of use before replacing. Three L1154F (LR44) alkaline batteries per temple (six total) are included

Easy to use push button on/off switches are located at the top of each temple

Part No.	Black Frame	
ESB6310STPLED ●●	AF	Clear



## PMXTREME®

### General Specifications

Weight: 27 gm  
 PD: 72 mm  
 Bridge: 14 mm  
 Lens base: 9 curve  
 Lens size diagonal: 78 mm  
 Lens size vertical: 46 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 103 mm  
 Overall width (hinge - hinge): 140 mm

### Materials

Lens: polycarbonate  
 Temple: nylon  
 Frame: nylon  
 Screw: stainless steel  
 Nosepiece: rubber  
 Temple tips: rubber

Part No.	Lens Marking	Temple Marking
ESB6310STP	2 - 1.2 P 1 F K N CE	CE P EN166 F
ESB6320STP	5 - 3.1 P 1 F K N CE	CE P EN166 F

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 K: Resistance to surface damage by fine particles  
 N: Filter with anti-fog  
 CE: Europe standard

### Temple Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact

## PMXTREME LED

### General Specifications

Weight: 50 gm  
 PD: 72 mm  
 Bridge: 14 mm  
 Lens base: 9 curve  
 Lens size diagonal: 78 mm  
 Lens size vertical: 46 mm  
 Lens thickness: 2.2 mm  
 Overall length (lens - tip): 103 mm  
 Overall width (hinge - hinge): 140 mm

### Materials

Lens: polycarbonate  
 Temple: nylon  
 Frame: nylon  
 Screw: stainless steel  
 Nosepiece: rubber  
 Temple tips: rubber

Part No.	Lens Marking	Temple Marking
ESB6310STPLED	2 - 1.2 P 1 F K N CE	CE P EN166 F

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 K: Resistance to surface damage by fine particles  
 N: Filter with anti-fog  
 CE: Europe standard

### Temple Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact

