

V2[®] Metal ANSI • CE • CSA •



RUBBER
NOSEPIECE

Spring loaded temples allows for easy positioning // Contemporary metal frame and temples fit most facial sizes // Custom imprinting available

Gun Metal Frame | 2 Variations

- SGM1810S Clear
- SGM1820S Gray



Part No.	Lens Marking	Frame Marking	General Specifications	Materials
SGM1810S	PZ87 + U6	P Z87 + / P c SEI Z94.3	Weight: 40 gm	Lens: polycarbonate
SGM1820S	PZ87 + U6 L2.5	P Z87 + / P c SEI Z94.3	PD: 68 mm	Frame: copper & brass alloy
			Bridge: 8 mm	Temples: copper & brass alloy
			Lens base: 9.75 curve	Hinge: polycarbonate
			Lens size diagonal: 85 mm	Screw: stainless steel
			Lens size vertical: 45.9 mm	Sleeve: copper & brass alloy
			Lens thickness: 2.2 mm	Nosepiece: copper + brass, alloy & polyvinyl chloride
			Overall length (lens - tip): 157 mm	Side shields: polycarbonate
			Overall width (hinge - hinge): 135 mm	
			Closest point between temple tips: 89 mm	
			Closest point between lens: 10.5 mm	

Lens Marking Symbols

P: Manufacturer's mark

+: High impact

Z87: ANSI standard for eye and face protection devices

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark

+: High impact

c SEI Z94.3: CAN/CSA standard for eye and face protection devices