

Velar™ ANSI • CE • CSA •



Built-in rubber nosepiece //
Co-injected rubber temples



Black Frame | 3 Variations

- SB10410D ●●● Clear
- SB10420D ●●● Gray
- SB10465D ●●● Ice Blue Mirror

Black and Red Frame | 1 Variation

- SBRF10445D ●●● Ice Orange Mirror

White and Blue Frame | 1 Variation

- SWBL10465D ●● Ice Blue Mirror

White and Red Frame | 1 Variation

- SWR10455D ●● Sky Red Mirror



SB 104



SWBL 104



SWR 104

Part No.	Lens Marking	Temple Marking
SB10410D	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3
SB10420D	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3
SB10465D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3
SBRF10445D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3
SWBL10465D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3
SWR10455D	P Z87 + S	P Z87 + / P c SEI CAN/CSA Z94.3

General Specifications
Weight: 28.5 gm
Bridge: 12.8 mm
Lens base: 8 curve
Lens size diagonal: 61.7 mm
Lens size vertical: 35.8 mm
Lens thickness: 2.2 mm
Overall length (lens - tip): 160 mm
Overall width (hinge - hinge): 127 mm
Closest point between temple tips: 82 mm

Materials
Lens: nylon
Nosepiece: thermoplastic rubber (TPR)
Frame: polycarbonate
Temple: polycarbonate + thermoplastic elastomer (TPE)
Logo emblem: polycarbonate
Hinge: nylon + polycarbonate
Screw: stainless steel

Lens Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
S: Special purpose
UV Filter Transmittance
U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
Z87: ANSI standard for eye and face protection devices
+: High impact
c SEI CAN/CSA Z94.3: CAN/CSA standard for eye and face protection devices