



















Venture 3[®] ANSI • CE • CSA • Ballistic •



Soft, adjustable nosepiece // Ventilated frame // Adjustable co-injected rubber temples // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

Black Frame | 9 Variations

	SB5710D		Clear
	SB5710DT		Clear H2X AF
	SB5710DTM		Clear H2MAX AF
	SB5720D		Gray
	SB5720DT		Gray H2X AF
	SB5730D		Amber
	SB5760D		Infinity Blue
	SB5770D		Silver Mirror
	SB5780D		I/O Mirror



Part No.	Lens Marking	Frame Marking
SB5710D	P + U6	P Z87 + / P c SEI Z94.3
SB5710DT	P + U6	P Z87 + / P c SEI Z94.3
SB5710DTM	P + U6 X	P Z87 + / P c SEI Z94.3
SB5720D	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB5720DT	P + U6 L2.5	P Z87 + / P c SEI Z94.3
SB5730D	P + U6	P Z87 + / P c SEI Z94.3
SB5760D	P + S	P Z87 + / P c SEI Z94.3
SB5770D	P + S	P Z87 + / P c SEI Z94.3
SB5780D	P + U6 L1.7	P Z87 + / P c SEI Z94.3

General Specifications
Weight: 28 gm
PD: 68 mm
Bridge: 12.8 mm
Lens base: 9.5 curve
Lens size diagonal: 82 mm
Lens size vertical: 46.6 mm
Lens thickness: 2.3 mm
Overall length (lens - tip): 150 - 163 mm
Overall width (hinge - hinge): 139.4 mm
Closest point between temple tips: 91 mm
Closest point between lens: 13.1 mm

Materials
Lens: polycarbonate
Frame: polycarbonate
Temple tips: polycarbonate & thermoplastic elastomers
Hinge: polycarbonate
Screw: stainless steel
Sleeve: polycarbonate
Nosepiece: bridge - polycarbonate & nose pad - polyvinyl chloride
Side shields: polycarbonate

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special Purpose
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices