



**PYRAMEX**  
Perform At Your Peak

**XSG®** ANSI CE CSA



FOAM  
PADDING



INCLUDES  
STRAP

Flame resistant foam padding

Strap has quick fit retainer

Interchangeable temples and strap included

Part No.	Black Frame
EGB4010ST ●●●	AF Clear H2X
EGB4020ST ●●●	AF Gray H2X
EGB4080ST ●●●	AF I/O Mirror



**XSG Kit** ANSI CE BALLISTIC



FOAM  
PADDING



INCLUDES  
STRAP



MULTI  
LENSES

Interchangeable lenses, temples, and strap

Black ballistic nylon case for storage

Passes MIL-PRF 32432 High Velocity  
Impact Standards

Part No.	Black Frame
EGB4010KIT ●●●	AF Clear H2X
	AF Gray H2X
	AF Amber H2X



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●), Canadian (CSA Z94.3) (●) or Ballistic (MIL-PRF-32432) (●) standards. For specific lens options visit our website or contact your sales representative.

## XSG® and XSG Kit

### General Specifications

Weight: 28 gm  
 PD: 68 mm  
 Bridge: 13.7 mm  
 Lens base: 8.0 curve  
 Lens size diagonal: 66.3 mm  
 Lens size vertical: 44 mm  
 Lens thickness: 2.3 mm  
 Strap length: 420 mm  
 Overall length (lens - tip): 163 mm  
 Overall width (hinge - hinge): 136.5 mm  
 Closest point between temples: 56 mm  
 Closest point between lens: 18.5 mm

### Materials

Lens: polycarbonate  
 Foam: polycarbonate & ethylene vinyl acetate (EVA)  
 Frame: nylon  
 Temples: polycarbonate & polyvinyl chloride (PVC)  
 Strap: polyester  
 Screw: stainless steel  
 Nosepiece: ethylene vinyl acetate (EVA)

Part No.	Lens Markings	Frame Markings
EGB4010ST	2 C - 1.2 P 1 F N CE	CE P EN166 F
EGB4020ST	5 -2.5 P 1 F N CE	CE P EN166 F
EGB4080ST	5 -1.7 P 1 F CE	CE P EN166 F
EGB4010KIT	2 C - 1.2 P 1 F N CE 5 -2.5 P 1 F N CE 2 - 1.2 P 1 F N CE	CE P EN166 F CE P EN166 F CE P EN166 F

### Lens Marking Symbols

#### Code - field of use

2 or 3: UV filter  
 5 or 6: Solar filter

#### Color perception

C: Unimpaired color perception

#### Protection class

1.2 - 6: Degree of visible light filtration

#### Optical class

1: High optical quality - no optical distortion

#### Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

#### Symbols

P: Manufacturer's mark  
 N: Filter with anti-fog  
 CE: Europe standard

### Frame Marking Symbols

#### Symbols

CE: Europe standard  
 P: Manufacturer's mark  
 EN166: CE specification for protective eyewear

#### Mechanical Strength

F: Low energy impact