

AerVOE[®] Military Digital Pattern Camo Paint - Aerosol Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know.

The following material safety data sheet covers the hazardous ingredients associated with more than one color aerosol paint. As per 29 CFR 1910.1200 paragraph (g), whenever the hazards associated with similar mixtures are the same, then one MSDS may be prepared to cover several products.

This MSDS covers the following AerVOE aerosol products:

1074 Green (474)	1075 Khaki (475)	1076 Coyote (476/499)	1077 Black (477)
1078 Urban Tan (478)	1079 Light Tan (479)	1080 Highland (480)	1081 Light Coyote (481)
1082 Desert Sand (500/503)	1083 Urban Gray (501/505)	1084 Foliage Green (502/504)	

Military Digital Pattern Camo Paint

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: AerVOE Industries Inc. **ADDRESS:** 1100 Mark Circle, Gardenville, NV 89410
INFORMATION PHONE: 775-783-3100 **EMERGENCY PHONE:** 1-800-424-3300
DATE REVISED: 07-29-10 **REASON REVISED:** Updated

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OCCUPATIONAL EXPOSURE LIMITS			
		OSHA PEL	ACGIH TLV	ACGIH STEL	LD50 SPECIES & ROUTE
Acetone (CAS 67-64-1)	30 - 80	1000 ppm	500 ppm	5600 mg / kg (Rat-Oral)	21000 ppm / 8 hr (Rat-Inh)
Hydrocarbon, Propellant (CAS 68-478-86-8)	10 - 30	1000 ppm	1000 ppm	N / AV	N / AV
n-Butyl Acetate (CAS 123-86-4)	5 - 10	150 ppm	150 ppm	N / AV	N / AV
Aromatic Petroleum Distillates (CAS 64742-98-8)	1 - 5	N / AV	300 ppm	N / AV	N / AV

*Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.
 NOTE: N / AV = Not Applicable N / AV = Not Available

1074MA

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS
BOILING POINT: N / AV
VAPOR DENSITY: Heavier than air
EVAPORATION RATE: Faster than n-Butyl Acetate

SPECIFIC GRAVITY (H2O=1): 0.8
SOLUBILITY IN WATER: Negligible
APPEARANCE AND ODOR: Opaque liquid with ketone odor

FLASH POINT: < 0° F (-18° C)

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, water spray.

FLAMMABLE LIMITS - LEL: 0.7% **UEL:** 13.0 %

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool containers exposed to heat or fire to prevent pressure build up. Self-contained breathing apparatus should be used if product is involved in fire.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Treat as cylinders of compressed gas. Closed containers may rupture due to pressure build up from extreme temperature.
FLAMMABILITY: Yes - Flammable aerosol under conditions of sparks, flame, or hot surfaces.
SENSITIVITY TO IMPACT: Do not puncture
SENSITIVITY TO STATIC DISCHARGE: Primarily vapors

SECTION V - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents.
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon Monoxide, Carbon Dioxide.
HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VI - HEALTH HAZARD DATA

INHALATION: Respiratory tract irritant. May cause dizziness, light-headedness and / or headaches.
SKIN CONTACT: Prolonged or repeated contact may cause irritation and dermatitis.
EYE CONTACT: Prolonged or repeated contact may cause irritation and dermatitis.
SKIN ABSORPTION: Not likely to be absorbed in toxic amounts under normal use.
INGESTION: Not likely in normal use, but swallowing large amounts may be harmful.
CARCINOGENICITY: The ingredients are not listed as a human carcinogen by IARC, ACGIH, NTP, or OSHA.
MUTAGENICITY: Not established.
MEDICAL CONDITION GENERALLY AGGRAVATED BY EXPOSURE: Not established.
EMERGENCY AND FIRST AID PROCEDURES - INHALATION: Remove from exposure, seek medical attention if signs/symptoms persist.
SKIN - Wash affected area with soap and water, remove contaminated clothing, seek medical attention if irritation persists.
EYES - Flush immediately with water for 15 minutes, seek medical attention if irritation persists.
INGESTION - Do NOT induce vomiting, drink plenty of water, seek medical attention.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate area. Prevent from entering a watercourse. Use an inert absorbent material and non-sparking type tools.
WASTE DISPOSAL METHOD: Dispose of in accordance with local, state and federal regulations. Do not incinerate closed containers.
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Do not store above 120° F (49° C). Do not store or use near heat, sparks or flame.
OTHER PRECAUTIONS: Do not smoke while using this product. Dust from sanding the dry paint film should be treated as a nuisance dust with a TLV of 15 mg / cubic meter.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: In areas with poor ventilation, use a NIOSH approved Organic Vapor Cartridge Respirator.
 For concentrations above the TLV (as defined in Section III), use a positive air supplied respirator.
VENTILATION: General ventilation to maintain exposure limits below TLVs as defined in Section II.
PROTECTIVE GLOVES: Chemical resistant gloves such as Neoprene or Nitrile rubber.
EYE PROTECTION: Safety glasses or goggles.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Not established.
WORK / HYGIENE PRACTICES: Avoid prolonged or repeated contact. Do not breathe vapors. Wash contaminated clothing prior to reuse.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.