



KEEPER GOALS

Heavy-Duty Team Shelters Safety Information and Maintenance Guidelines

- Inspect for damage that may have occurred during shipping. If damage has occurred notify trucking company immediately.
- Securely anchor the shelter at ALL times, except when being moved. Follow instructions on included sheets to safely anchor the shelter. Shelters should be re-anchored after moving.
- Shelters shall not be left unattended and never leave children unsupervised around shelters.
- Always instruct players, managers, coaches, trainers, teachers, maintenance and all other personnel who might come into contact with the shelter on the safe handling of and potential dangers associated with the shelter.
- Always exercise extreme caution when moving the shelters and allow adequate manpower to move the shelter. Shelters should only be moved by authorized and trained personnel.
- NEVER allow anyone to climb on the shelter.
- Shelters should only be located on a LEVEL surface, NEVER on a slope or hill area.
- Anchor the shelter to the ground or chain one shelter to another (face to face) before leaving the field or when the shelters are not in use for extended periods of time.
- Frequently inspect all welds and connections to make sure welds are not cracked and that all joints and connections are secure before using shelter.
- Frequently inspect shelters for nicks and scratches that could lead to rust and for other signs of rust. Rust is not a condition of the warranty. The best rust protection is early detection. If needed, sand and re-paint.
- Removing snow from the top of shelters is recommended.
- Heavy-Duty Team Shelters are not meant to be classified as water-tight. The shelters are caulked to help prevent water from dripping inside the shelter. Heavy-Duty Team Shelters are caulked on the top and slightly down the back – they are not caulked all the way down the entire arch. We provide an extra tube of caulk with your shelter shipment in case you need to touch up any areas where the caulking may have separated from the frame during transit. Additional caulking may be required to stop any leaks that may occur over time. Occasionally the caulk will move when the shelters are moved. We recommend you regularly check to see if touch-up caulk is needed. (Continued)

- Shelters may be sandblasted and re-finished to further extend the life of the shelter. Contact Keeper Goals for more information on re-finishing shelters.
- The lexan panels may discolor over time. Ultraviolet rays will eventually weaken the lexan material. Although it may last longer, it is recommended that the lexan panels be replaced every 5-7 years.
- **Any modifications to this or any Keeper Goals product will void any and all warranties.**

12400 West Silver Spring Drive Butler, WI 53007
(P) 262-781-7800 / (P) 800-594-5126
Visit our website at keepergoals.com
Email at info@keepergoals.com