



KEEPER GOALS

Heavy-Duty Team Shelters – Special Notes

Removal of Protective Film Covering on Polycarbonate Sheets

- After the shelter has been removed from the truck, the protective film covering on both sides of the polycarbonate sheets should be removed as soon as possible if the shelters are being stored outside before actually using them!
- If a portion of the protective film is between the polycarbonate sheet and the shelter frame plate, using a razor blade or utility knife, carefully scribe the protective film along the edge of the frame plate. After it is scribed, you should be able to remove the protective film. If you pull it quickly it comes off much easier.

Cleaning of Polycarbonate Sheets

- Never use harsh chemicals to clean the polycarbonate sheets. For cleaning, use water or you may use water with a very mild dish soap.

Caulking

- Heavy-Duty Team Shelters are not meant to be classified as water-tight. The shelters are caulked to help prevent water from dripping inside the shelter. Heavy-Duty Team Shelters are caulked on the top and slightly down the back – they are not caulked all the way down the entire arch. We provide an extra tube of caulk with your shelter shipment in case you need to touch up any areas where the caulking may have separated from the frame during transit. Additional caulking may be required to stop any leaks that may occur over time. Occasionally the caulk will move when the shelters are moved. We recommend you regularly check to see if touch-up caulk is needed.

(Continued)

Touch-Up Paint

- **We have included a can of spray paint for touchup in case of damage during shipping. It is also important to regularly touch up any painted surface that may have been nicked or scratched over time.**

12400 West Silver Spring Drive Butler, WI 53007
(P) 262-781-7800 / (P) 800-594-5126
Visit our website at keepergoals.com
Email at info@keepergoals.com