

## ED Series

### Sunlite 03668-SU MH175/C/U/MED M57 Metal Halide Lamp, 175 Watts, Probe Start, Medium Base (E26), ED17, 10,000 Hours Life, 13000 Lumen, White Coated Finish, 4200K

Metal Halide

#### **DESCRIPTION:**

Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance. These 175 watt metal halide bulbs have a bright 13000 lumen output. They are medium base (E26), ED17 bulbs with an average life span of 10,000 hours. Use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. ANSI Code M57. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses. Bulb measurements are 2.186 inches in diameter, 5.376 inches tall.

#### **FEATURES:**

- **METAL HALIDE** - Sunlite high intensity discharge lamps are perfect for outdoor lighting and commercial interiors. These energy efficient HID lamps offer exceptional efficacy, great color rendition, have a long service life and excellent lumen maintenance.
- **HIGH INTENSITY DISCHARGE** - This 175 watt bulb puts out a bright 13000 lumens of light. Color temperature is 4200K. White Coated glass bulb.
- **MEDIUM BASE** - Standard medium base (E26) for use in street lights, parking lot fixtures, perimeter lighting, and other commercial and industrial lighting applications. Bulb measurements 2.186 inches diameter, 5.376 inches tall.
- **LONG LIFE** - These probe start bulbs feature a long average lifespan of 10,000 hours.
- **ANSI CODE M57** - This metal halide bulb is for use in M57 ballast fixtures. Confirm ANSI Code to help determine the correct bulb for your fixture and the ballast it uses.



**SPECIFICATIONS:****General Characteristics**

<b>Bulb Shape</b>	ED17
<b>Ansi code</b>	M57
<b>Average Rated Hours</b>	10000
<b>Finish</b>	Coated
<b>Base</b>	Medium Screw (E26)
<b>Average Life Span Years</b>	9

**Electrical Characteristics**

<b>Watts</b>	175
--------------	-----

**Light Characteristics**

<b>Lumens Brightness</b>	13000
<b>Color Rendering Index CRI</b>	65
<b>Emitted Color</b>	Cool White
<b>Color Temperature Kelvin</b>	4200K

**Product Dimensions**

<b>MOL (in)</b>	5.376
<b>Diameter (in)</b>	2.186"
<b>Item Dimension (in)</b>	(W) 2.19 (H) 5.38 (D) 2.19
<b>Package Dimension (in)</b>	(W) 2.3 (H) 5.9 (D) 2.4
<b>Package Weight (lb)</b>	0.200

**Product Data**

<b>Case Unit Rate</b>	12
<b>Pack Size</b>	1
<b>Item UPC</b>	653703036687
<b>Warranty Years</b>	1

**VARIATIONS:**



03668-SU



03648-SU



03623-SU



03623-SU

<i>Item Number</i>	<i>Description</i>	<i>Watts</i>	<i>Lumens</i>	<i>CRI</i>	<i>Kelvin Color</i>	<i>Hours</i>	<i>Pack</i>
03668-SU	MH175/C/U/MED	175	13000	65	4200K CW	10000	1
03648-SU	MH100/C/U/MED	100	7700	65	4000K CW	15000	1
03623-SU	MH150/C/U/MED	150	13000	65	4000K CW	10000	1
03623-SU	MH150/C/U/MED	150	13000	65	4000K CW	10000	1