

ST Series

Sunlite 28 Watt T5 High Performance Straight Tube, Mini Bi-Pin Base, Super White

T5 High Performance Straight Tube

DESCRIPTION:

Sunlite fluorescent lamps are very popular for use in office and other lighting applications. The characteristics of fluorescent lamps vary type of lamp. Fluorescents lamps are used so widely due to their low operating costs and because they are efficient, last for years, and are high quality and rapid starting. Fluorescent lamps can cost significantly less to operate over their lifetime than incandescent lamps. Life ratings for fluorescent lamps range from 6,000 to 36,000 hours based on the industry standard of 3 burning hours per start. Also, rapid start and instant start lamps typically start within 1 second of being turned on. The High Performance and High Output versions also give you and even better efficacy and energy efficiency. Look for a higher CRI for improved light quality. Sunlite 30342-SU F28T5/850 5000K Color Temperature T5 High Performance Straight Tube Fluorescent 28 Watt lamp features a Mini Bi Pin base, provides a light output of 2500 lumens at a Color Rendering Index (CRI) of 82 and can last an average of 20000 hours.

FEATURES:

- 28-Watt
- 5000K Color Temperature
- 20,000 hour average lamp life
-
-



SPECIFICATIONS:

General Characteristics

Bulb Shape	T5
Average Rated Hours	20000
Base	Miniature Bi-Pin (G5)
Average Life Span Years	18

Electrical Characteristics

Watts	28
--------------	----

Light Characteristics

Lumens Brightness	2500
Color Rendering Index CRI	82
Emitted Color	Super White
Color Temperature Kelvin	5000K

Additional Features

Rohs Compliant	Yes
-----------------------	-----

Product Dimensions

Size	4 Foot
MOL (in)	45.80
Diameter (in)	0.625"
Item Dimension (in)	(W) 0.63 (H) 0.63 (D) 45.8
Package Dimension (in)	(W) 0.64 (H) 0.64 (D) 45.6
Package Weight (lb)	0.260

Product Data

Case Unit Rate	40
Pack Size	1
Item UPC	653703303420



VARIATIONS:



<i>Item Number</i>	<i>Description</i>	<i>Watts</i>	<i>Lumens</i>	<i>CRI</i>	<i>Kelvin Color</i>	<i>Hours</i>	<i>Pack</i>
30342-SU	F28T5/850	28	2500	82	5000K SW	20000	1
30330-SU	F28T5/830	28	2500	82	3000K WW	20000	1
30335-SU	F28T5/835	28	2500	82	3500K NW	20000	1
30340-SU	F28T5/841	28	2500	82	4100K CW	20000	1
30345-SU	F28T5/865	28	2500	82	6500K DL	20000	1