

## R Series

### Sunlite 40456 LED R14 Mini Reflector Floodlight Light Bulb, 4 Watts (25W Equivalent), 250 Lumens, Intermediate (E17) Base, Dimmable, ETL Listed, 2700K Warm White, 3 Count

R14 Reflector

#### DESCRIPTION:

Upgrade your incandescent light bulbs with energy-efficient led bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 25,000 hours, you will replace difficult-to-reach bulbs less often. You will save maintenance costs and save energy at the same time. They feature an E17 intermediate base and have the ability to be dimmed. This Sunlite R14 led bulb is ETL Listed. Unlike incandescent bulbs, these bulbs contain no harmful chemicals and do not require special handling or disposal.



#### FEATURES:

- **UPGRADE TO LED** - Replace inefficient incandescent bulbs with energy saving LED bulbs. These R14 Mini Reflector Floodlight bulb got you covered. These bulbs are ideal for many applications such as track fixtures, china cabinets, curio cabinets, closets, desk lamps, and so much more!
- **ENERGY EFFICIENT:** Get the same output as a 25 Watts Bulb while only using 4 watts of electricity, which makes you save a significant amount on your energy bill. The LED bulb costs only 0.48 per year to operate.
- **DIMMABLE** - Emits a dimmable and comfortable, warm white light at 2700K, generating a relaxing atmosphere in every room of your home. Ideal for fixtures with an intermediate (E17) base. Color Rendering Index rating of 80 for more vivid and true colors
- **LONG LIFE** - With a life span of up to 25,000 hours, you will replace difficult-to-access bulbs less often. You will save maintenance costs and save energy at the same time
- **A SAFER CHOICE** These bulbs contain no mercury or other harmful chemicals. They feature a long life so you replace them less often. More energy efficient than incandescent and compact fluorescent bulbs. These lamps are ETL Listed for Damp Location use



## SPECIFICATIONS:

### General Characteristics

<b>Bulb Shape</b>	R14
<b>Average Rated Hours</b>	25000
<b>Base</b>	Intermediate Screw (E17)
<b>Average Life Span Years</b>	23
<b>Dimmable</b>	Yes

### Electrical Characteristics

<b>Watts</b>	4
<b>Volts</b>	120
<b>Equivalent Wattage</b>	25
<b>LED Chip Manufacturer</b>	Bridgelux
<b>Power Factor</b>	0.7
<b>Temperature</b>	-20° to 45°

### Light Characteristics

<b>Lumens Brightness</b>	280
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	Warm White
<b>Color Temperature Kelvin</b>	2700K
<b>Beam Angle</b>	105°

### Additional Features

<b>Safety Rating Mark</b>	UL Listed - Damp Location
---------------------------	---------------------------

### Product Dimensions

<b>MOL (in)</b>	2.5
<b>Diameter (in)</b>	1.57
<b>Item Dimension (in)</b>	(W) 1.7 (H) 2.5 (D) 1.7
<b>Package Dimension (in)</b>	(W) 1.89 (H) 2.8 (D) 5.5
<b>Package Weight (lb)</b>	0.28

### Product Data

<b>Case Unit Rate</b>	6
<b>Pack Size</b>	3
<b>Item UPC</b>	653703404561
<b>Warranty Years</b>	3
<b>Package Type</b>	Box

