

## MR Series

### Sunlite 40765 MR11 Halogen Reflector Bulb, 10 Watt, 30° Narrow Flood, 12 Volt, 110 Lumens, 2000 Hour Life Span, Dimmable, GU4 Base, Cover Guard, 3200, ANSI JCR, Ceiling Fixtures, Lanterns 6-Pack

MR11 Mini Reflector

#### DESCRIPTION:

These Sunlite 10-watt MR11 dimmable halogen lamps have a 30° Narrow Flood beam angle and a standard GU4 base. They feature Cover Guard and prismatic reflector. With a 2000 hour life span. Designed for use in 12-volt lamps, ceiling fixtures, track lighting, display case lighting, and lanterns. 80 CBCP. These mini reflector bulbs are 1.37 inches in diameter and 1.33 inches in overall height. ANSI Code JCR.

#### FEATURES:

- **MR11 LAMPS** - These 10-watt halogen bulbs feature Cover Guard and prismatic reflector.
- **NARROW FLOOD BEAM** - 30° Narrow Flood beam angle and standard GU4 base. These mini reflector bulbs are 1.37 inches in diameter and 1.33 inches in overall height.
- **DIMMABLE** - Fully dimmable when installed in a fixture with dimming control. 110 Lumen output. White light at 3200 Kelvin.
- **LONG LIFE** - Long a 2000 hour life span.
- **MULTIPLE USES** - Designed for use in 12-volt lamps, ceiling fixtures, track lighting, display case lighting, and lanterns. 80 CBCP. ANSI Code JCR.



## SPECIFICATIONS:

### General Characteristics

|                                |             |
|--------------------------------|-------------|
| <b>Bulb Shape</b>              | MR11        |
| <b>Average Rated Hours</b>     | 2000        |
| <b>Base</b>                    | 2-Pin (GU4) |
| <b>Average Life Span Years</b> | 2           |
| <b>Lens Louver</b>             | Cover Guard |

### Electrical Characteristics

|              |    |
|--------------|----|
| <b>Watts</b> | 10 |
| <b>Volts</b> | 12 |

### Light Characteristics

|                                  |              |
|----------------------------------|--------------|
| <b>Lumens Brightness</b>         | 110          |
| <b>Color Rendering Index CRI</b> | 100          |
| <b>CBCP</b>                      | 890          |
| <b>Emitted Color</b>             | Bright White |
| <b>Color Temperature Kelvin</b>  | 3200K        |
| <b>Beam Angle</b>                | 30°          |
| <b>Beam Angle Description</b>    | Narrow Flood |

### Additional Features

|                 |   |
|-----------------|---|
| <b>Title 20</b> | Not for sale in the State of California |
|-----------------|---|

### Product Dimensions

|                               |                            |
|-------------------------------|----------------------------|
| <b>MOL (in)</b>               | 1.3                        |
| <b>Diameter (in)</b>          | 1.4                        |
| <b>Item Dimension (in)</b>    | (W) 1.35 (H) 1.34 (D) 1.35 |
| <b>Item Weight (lb)</b>       | 0.030                      |
| <b>Package Dimension (in)</b> | (W) 2.4 (H) 3.7 (D) 5.4    |
| <b>Package Weight (lb)</b>    | 0.350                      |

### Product Data

|                       |              |
|-----------------------|--------------|
| <b>Case Unit Rate</b> | 20           |
| <b>Pack Size</b>      | 6            |
| <b>Item UPC</b>       | 653703407654 |
| <b>Package Type</b>   | Box          |



DIMMABLE