

R Series

Sunlite 80425 LED R14 Mini Reflector Floodlight Light Bulb, 4 Watts (25W Equivalent), 250 Lumens, Intermediate (E17) Base, Dimmable, ETL Listed, 3000K Warm White, 1 Count

R14 Reflector

DESCRIPTION:

Upgrade your incandescent light bulbs with energy-efficient led bulbs from Sunlite. They are instant on at full brightness with no buzzing or flickering. With a life span of up to 25,000 hours, you will replace difficult-to-reach bulbs less often. You will save maintenance costs and save energy at the same time. They feature an E17 intermediate base and have the ability to be dimmed. This Sunlite R14 led bulb is ETL Listed. Unlike incandescent bulbs, these bulbs contain no harmful chemicals and do not require special handling or disposal.

FEATURES:

- UPGRADE TO LED Replace inefficient incandescent bulbs with energy saving LED bulbs. These R14 Mini Reflector Floodlight bulb got you covered. These bulbs are ideal for many applications such as track fixtures, china cabinets, curio cabinets, closets, desk lamps, and so much more!
- ENERGY EFFICIENT: Get the same output as a 25 Watts Bulb while only using 4 watts of electricity, which makes you save a significant amount on your energy bill. The LED bulb costs only 0.48 per year to operate.
- DIMMABLE Emits a dimmable and comfortable, warm white light at 2700K, generating a relaxing atmosphere in every room of your home. Ideal for fixtures with an intermediate (E17) base. Color Rendering Index rating of 80 for more vivid and true colors
- LONG LIFE With a life span of up to 25,000 hours, you will replace difficult-to-access bulbs less often. You will save maintenance costs and save energy at the same time
- A SAFER CHOICE These bulbs contain no mercury or other harmful chemicals. They feature a long life so you replace them less often. More energy efficient than incandescent and compact fluorescent bulbs. These lamps are ETL Listed for Damp Location use



sunlite

SPECIFICATIONS:

General Characteristics

Product Dimensions

000 ermediate Screw (E17) 20 (12.5 mm solids, Not otected from liquids) s astic & Aluminum 0 d Headboard Lighting, Color ndering Index 80 (CRI), nge Hood Lighting, Reading mp.	Diameter (in) Item Dimension (in) Package Dimension (in) Package Weight (lb) Product Data Case Unit Rate Pack Size Item UPC Warranty Years Package Type	1.57 (W) 1.7 (H) 2.5 (D) 1.7 (W) 1.8 (H) 2.8 (D) 1.9 0.1 6 1 653703804255 BX Box
, ,		
0~45?		
	ermediate Screw (E17) 20 (12.5 mm solids, Not otected from liquids) s astic & Aluminum 0 d Headboard Lighting, Color ndering Index 80 (CRI), nge Hood Lighting, Reading mp,	ermediate Screw (E17) ltem Dimension (in) Package Dimension (in) Package Weight (lb) Product Data Case Unit Rate Pack Size Item UPC Warranty Years Package Type d Headboard Lighting, Color ndering Index 80 (CRI), nge Hood Lighting, Reading mp,

Light Characteristics

Lumens Brightness	250
Color Rendering Index CRI	80
Emitted Color	Warm White
Color Temperature Kelvin	3000K
Beam Angle	105°
Flicker	no

Additional Features

Safety Rating Mark

ETL - Damp Location



Catalog # 80425-SU R14/LED/N/E17/4W/30K