

G Series

Sunlite 80789-SU LED G16.5 Filament Style Globe Light Bulb, 5 Watts (60W Equivalent), 500 lumens, Dimmable, Candelabra Base (E12), UL Listed, 50K Super White, 1 Pack

Filament

DESCRIPTION:

The Sunlite LED G16.5 globe bulbs are energy efficient, and a long life replacement for incandescent bulbs in decorative fixtures. These dimmable bulbs put out at much light as a 60 watts bulb while only using 5 watts of electricity. Long 15, 000 hours life span means you'll save money and replace difficult to reach bulbs less often. Super white color temperature (5000K) with 500 lumen output. Color rendering index (CRI) of 85. Candelabra Base (E12) compatible with a variety of decorative applications such as chandeliers, wall sconces and ornamental lights. Annual operating costs of \$0.60 a year based on 3 hours a day use at \$0.11/kWh. UL Listed for safety and quality. Bulb measures 3.5 inches in overall height and 2 inches in diameter. This Product has a one-year warranty.



- UPGRADE TO LED Upgrade your lighting to LED technology with these Candelabra Base globe bulbs. These bulbs put out at much light as a 60 watts bulb while only using 5 watts of electricity. High color rendering index (CRI) of 85. LED technology means they are cool to the touch when lit and instant-on at full brightness.
- ■DIMMABLE These Candelabra Base (E12) Light bulbs are dimmable when installed in a lamp or fixture with dimming capabilities, creating your favorite tone depending on your mood in any space. Warm white color temperature (3000K) with 500 lumen output.
- LONG LIFE BULBS With LED technology you save cost and the hassle of replacing hard to reach bulbs. With an average life of 15, 000 hours you'll get years of reliable service. The annual energy cost is a low \$0. 60 per bulb (based on 3 hours/day at \$0. 11 per/kWh).
- G16.5 GLOBE SHAPE Use these Antique LED G16.5 globe shaped decorative bulbs as a replacement for incandescent G16.5 bulbs in a variety of decorative applications such as, chandeliers, pendants, wall sconces and ornamental lights. Also used for living rooms, dining rooms, bedroom, bathroom vanities, lamps, display signs and other visible fixtures.





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish Base G16.5

15000

Clear

Yes

Glass

Medium Screw (E12)

IP20 (12.5 mm solids, Not

protected from liquids)

Average Life Span Years Ingress Protection

Dimmable Material

Electrical Characteristics

Watts 5
Volts 120
Equivalent Wattage 60
Power Factor 0.7
Temperature -20?-40?

Light Characteristics

Lumens Brightness500Color Rendering Index CRI85

Emitted Color
Color Temperature Kelvin
Flicker
Super White
5000K
300°

Additional Features

Safety Rating Mark
UL Rated Enclosed Fixtures

UL Listed - Damp Location Yes

Product Dimensions

 MOL (in)
 3.35

 Diameter (in)
 1.97

 Item Dimension (in)
 (W) 2.09 (H) 3.94 (D) 2.09

 Package Dimension (in)
 (W) 4.2 (H) 2.2 (D) 2.2

 Package Weight (lb)
 0.050

Product Data

 Case Unit Rate
 6

 Pack Size
 1

 Item UPC
 653703807898

 Warranty Years
 2

 Package Type
 Box





VARIATIONS:



Item Number	Description	Watts	Eq Watts	Lumens	CRI	Kelvin Color	Hours	Pack
80789-SU	G16.5/LED/FS/5W/E12/CL/50K	5	60	500	85	5000K SW	15000	1