

T Series

Sunlite 80871 LED Metal Halide, HPS, HID High Bay Replacement Light Bulb, 60 Watts (150W Equivalent) 9000 Lumen, Mogul (E39) Base, 120-277 Volts, Dimmable, UL Listed, 5000K Daylight, 1 Count



DESCRIPTION:

Sunlite led high bay bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warmup time. Each bulb gives off a bright 9000 lumen at 5000K Daylight color temperature. Provides as much light as a 150 watt bulb while only using 60 watts of electricity. With a 50,000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications. UL Listed for Damp Location Installation. They have a mogul (E39) base and a wide flood 120 degree beam spread.

FEATURES:

- **UPGRADE TO LED** - Our Sunlite LED High Bay bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. They are instant on at full brightness with no warmup time
- **DLC Certified** - These bulbs are DLC certified for energy efficiency, at 9000 lumens this high bay replacement led gives out as much light as a 150 watt bulb while only using 60 watts of electricity! Estimated yearly energy cost is a low \$7.23 (Based on 3 hours/day use at \$0.11/kWh)
- **LONG LIFE** - With a 50000 hour lifespan these led light bulbs Replace Metal Halide, HPS and HID lamps and will provide significant savings in electricity over their lifetime it will also require you to replace hard to reach bulbs less often
- **UL LISTED** - These bulbs are UL Listed for Damp Location installations. Our high bay retrofits are multi-volt they can use 120-277 volts of electricity and have a mogul (E39) base
- **BALLAST BYPASS REQUIRED** - These LED bulbs do not require a ballast. You must bypass the ballast in all fixtures before installing these bulbs. Simple instructions can be found online or consult an electrician for more information

SPECIFICATIONS:

General Characteristics

Bulb Shape	Other
Average Rated Hours	50000
Finish	White
Base	Mogul Screw (E39)
Average Life Span Years	46
Ingress Protection	IP44 (1 mm solids, Splashing of water)
Dimmable	Yes
Material	PC & Aluminum

Electrical Characteristics

Watts	60
Volts	120-277
Equivalent Wattage	150
LED Chip Manufacturer	SMD2835
Power Factor	0.9
Temperature	-4 ~122

Light Characteristics

Lumens Brightness	9000
Color Rendering Index CRI	80
CBCP	120°
Emitted Color	Daylight
Color Temperature Kelvin	5000K

Additional Features

Safety Rating Mark	UL Listed - Damp Location
Safety Rated For Canada	Yes
Safety Rated For USA	Yes
DLC	Yes
DLC Classification	Standard

Product Dimensions

MOL (in)	9.17
Diameter (in)	6.7
Item Dimension (in)	(W) 6.7 (H) 9.05 (D) 6.7
Package Dimension (in)	(W) 7.2 (H) 10 (D) 7.2
Package Weight (lb)	1.68

Product Data

Case Unit Rate	4
Pack Size	1
Item UPC	653703808710
Warranty Years	5

