

T Series**Sunlite 81265-SU LED T32 Super Bright High Lumen Corn Light Bulb, 20 Watts (225W Equivalent) 2600 Lumens, Medium e26 Base, 120-277 Multi Volt, Non-Dimmable, 50K-Super White, UL Listed-Wet Location**

High Lumen Lamps

DESCRIPTION:

Sunlite Bullet LED T36 corn bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warm up time. Each bulb contains 53 LEDs giving off a bright 2600 lumen at 5000K Super White color temperature. Provides as much light as a 225 watt bulb while only using 20 watts of electricity. With a 50000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications. UL Listed for Damp Location Installation. They have a medium base (E26) and can be used with mogul base (E39) adapters (not included). The 220 degree beam angle gives a broader spread than UFO bulbs and more downlight than corn bulbs.

FEATURES:

- **UPGRADE TO LED** - These LED T32 corn bulbs are the perfect replacement for metal halide, mercury vapor, and high/low pressure sodium bulbs in high bay fixtures. These bulbs are instant on at full brightness with no warm up time.
- **ENERGY EFFICIENT** - These bulbs give out as much light as a 225 watt incandescent bulb while only using 20 watts of electricity. Estimated yearly energy cost is a low \$2.41. (Based on 3 hours/day use at \$0.11/kWh)
- **HIGH LUMEN OUTPUT** - LED Bullet Bulbs provide 220 degree lighting coverage giving them a broader spread than UFO bulbs and more downlight than corn bulbs. Each bulb contains 53 LEDs and gives off a bright 2600 lumen output with Super White 5000K color temperature.
- **LONG LIFE** - With a 50,000 hour lifespan these bulbs will provide significant savings in electricity over their lifetime and require less maintenance for hard to reach fixtures. Ideal for warehouses, garages, workshops, barns, retail stores, gyms and other commercial/industrial applications.
- **UL LISTED** - These bulbs are UL Listed for Wet Location installations. They have a medium base (E26) and can be used with mogul base (E39) adapters (not included). For use in 120-277 volt fixtures. Ingress protection (IP) rating of 44.



SPECIFICATIONS:

General Characteristics

Bulb Shape	T32
Average Rated Hours	50000
Finish	White
Base	Medium Screw (E26)
Average Life Span Years	46
Ingress Protection	IP44 (1 mm solids, Splashing of water)
Dimmable	No
Material	Aluminum & PC

Electrical Characteristics

Watts	20
Volts	120-277
Equivalent Wattage	225
LED Chip Manufacturer	3825
Power Factor	0.9
Temperature	-20-45°

Light Characteristics

Lumens Brightness	2600
Color Rendering Index CRI	80
Emitted Color	Super White
Color Temperature Kelvin	5000K
Beam Angle	220°
Flicker	30%

Additional Features

Safety Rating Mark	UL Listed - Wet Location
---------------------------	--------------------------

Product Dimensions

MOL (in)	5.75
Diameter (in)	3.15
Package Dimension (in)	(W) 6.1 (H) 3.5 (D) 3.4
Package Weight (lb)	1.97

Product Data

Case Unit Rate	6
Pack Size	1
Item UPC	653703812656
Warranty Years	3
Package Type	Box

