

Sunlite 85123 LED Mini Wall Pack Outdoor Fixture, Tunable 8W/10W/15W/25W Power, 3500 Lumens, Tunable 30K/40K/50K Color, Dimmable, D2D Photocell, ETL Listed, Bronze, For Residential & Commercial Use

DESCRIPTION:

Sunlite LED Mini Wall Pack light fixtures are intended to provide ample outdoor lighting. You can choose between 3000K Warm White, 4000K Cool White, and 5000K Daylight at the back of the fixture. Take control of the light emitted with its tunable wattage of 8W/10W/15W/25W. These commercial grade fixtures have a weather-resistant bronze die-cast and a long-lasting clear polycarbonate lens. With a long life-span of 50,000 hours, these fixtures have the highest dust protection level and can tolerate low-pressure water jets from all angles, thanks to their IP 65 classification. It can be dimmed when installed with an LED-compatible 0-10v dimmer. Built-in photocell for automatic dusk to dawn operation. They provide up to a bright 3900-lumen output depending on the wattage. Ideal for security and general-purpose lighting along building perimeters, entryways, and anywhere extra lighting is required. These fixtures are ETL Listed for wet location installation and not rated for enclosed fixtures. They operate on 120-277-volt service. Fixture Dimension 8.2" H x 5.5" W x 3.4" L.



- COLOR & POWER TUNABLE Sunlite LED Mini Wall Pack light fixtures are intended to provide ample outdoor lighting. It has cutting-edge technology that allows you to customize the color temperature and power before installation. You can choose between 3000K Warm White, 4000K Cool White, and 5000K Daylight at the back of the fixture. Take control of the light emitted with its tunable wattage of 8W/10W/15W/25W.
- MULTIPLE OUTDOOR USES These commercial grade fixtures have a weather-resistant bronze die-cast and a long-lasting clear polycarbonate lens. With a long life-span of 50,000 hours, these fixtures have the highest dust protection level and can tolerate low-pressure water jets from all angles, thanks to their IP 65 classification.
- DIMMABLE It can be dimmed when installed with an LED-compatible 0-10v dimmer.





tage. Ideal for security

building perimeters,
ting is required.
TL Listed for wet
or enclosed fixtures.

8.2" H x 5.5" W x 3.4" L



ice. Fixture Dimension



SPECIFICATIONS:

General Characteristics

Average Rated Hours

Finish

Average Life Span Years

Ingress Protection

Dimmable

Dimming Type

Dimming Percentage

Material

Lens Material Lens Finish

50000 **Bronze**

46

IP65 (Dust-tight solids, Water

jets)

Yes

0-10V Low Voltage

0-100%

Aluminum + PC Polycarbonate

Frosted

Product Dimensions

Item Dimension (in) Package Dimension (in)

Package Weight (lb)

Product Data

Case Unit Rate Pack Size

Item UPC

Warranty Years

(W) 5.5 (H) 8.2 (D) 3.4 (W) 3.8 (H) 6.75 (D) 8.5

2.67

10 1

653703851235

5

Electrical Characteristics

Watts **Volts**

LED Chip Manufacturer

Power Factor

Temperature

8/10/15/25 120-277

3030

0.92

-40°F - 104°F

Light Characteristics

Lumens Brightness

Color Rendering Index CRI

Emitted Color

Color Temperature Kelvin

1160/1450/2175/3625

70

CCT Tunable 30K/40K/50K

Fixture Characteristics

Mounting Fixture Technology

Use Location

Wall LED Outdoor

Additional Features

Safety Rating Mark

Safety Rated For Canada Safety Rated For USA

DLC

DLC Classification

Mercury Free

ETL Listed - Wet Location

Yes Yes

Yes

Premium

Yes







