

## DESCRIPTION:

Sunlite's LED circular pole-top fixtures provide ample lighting for outdoor areas while saving energy. Each dimmable fixture contains 80 high output LEDs that project downward and mount on 3-inch posts (not included). Perfect for parking areas, airports, parks, and more. These commercial grade fixtures feature a frosted bronze finish on the rust-proof aluminum frame and a frosted polycarbonate lens. Both are designed to resist the elements for years of maintenance-free service. They are also UL Listed for wet location installation and DLC Listed for quality and efficiency.

## FEATURES:

- 
- 
- 
- 
- 



## SPECIFICATIONS:

### General Characteristics

<b>Average Rated Hours</b>	50000
<b>Finish</b>	Bronze
<b>Average Life Span Years</b>	46
<b>Ingress Protection</b>	IP65 (Dust-tight solids, Water jets)
<b>Dimmable</b>	Yes
<b>Dimming Type</b>	0-10V Low Voltage
<b>Dimming Percentage</b>	10-100%
<b>Material</b>	Die-casting
<b>Lens Material</b>	Glass
<b>Lens Finish</b>	Clear

### Electrical Characteristics

<b>Watts</b>	75
<b>Volts</b>	120-277V
<b>LED Chip Manufacturer</b>	LUMILEDS2835
<b>Power Factor</b>	0.92
<b>Temperature</b>	-40°F - 122°F

### Light Characteristics

<b>Lumens Brightness</b>	9750
<b>Color Rendering Index CRI</b>	80
<b>Emitted Color</b>	CCT Tunable
<b>Color Temperature Kelvin</b>	30K/40K/50K
<b>Beam Angle</b>	115°
<b>Flicker</b>	No

### Fixture Characteristics

<b>Shape</b>	Round
<b>Number of Lights</b>	1
<b>Mounting</b>	Pole
<b>Fixture Technology</b>	LED
<b>Use Location</b>	Outdoor

### Additional Features

<b>Safety Rating Mark</b>	UL Listed - Wet Location
<b>DLC</b>	Yes
<b>DLC Number</b>	PL25YSW303DC
<b>DLC Classification</b>	Standard

### Product Dimensions

<b>MOL (in)</b>	20.69
<b>Diameter (in)</b>	15
<b>Item Dimension (in)</b>	(W) 15 (H) 20.69 (D) 15
<b>Package Dimension (in)</b>	(W) 21 (H) 7.8 (D) 29
<b>Package Weight (lb)</b>	14.56

### Product Data

<b>Item UPC</b>	653703855264
<b>Warranty Years</b>	5



## **ACCESSORIES:**



Catalog # 85511-SU  
**MV**

Catalog # 85538-SU  
**TOP**