

Sunlite 87707 LED 6-Inch Round Recessed Slim Downlight, 12 Watts (75W=), 950 Lumens, Tunable 27K/30K/35K/40K/50K Color, 90 CRI, Energy Star & ETL Listed, White, for Residential & Commercial Use Slim

### **DESCRIPTION:**

This 6-inch LED Recessed Slim Downlight from Sunlite features innovative technology that allows you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference. using a switch located on the back of the fixture. Its slim feature allows them to be installed in limited clearance areas. Use for new installations or as a retrofit replacement for existing recessed lighting. LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. Comparable output to a 75watt bulb while only using 12 watts of electricity. Estimated annual energy costs of \$1.45 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Built-in long-life LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. This fixture is ETL Listed for Wet Location Installation. Good for commercial or residential installations. Suitable for entryways, bedrooms, kitchens, hallways, bathrooms, and more. Tested Compatible Dimmers: LUTRON: DVELV-300P-WH, PWCL-153PH, DVCL-153P, CTCL-153P, S-600H-WH-CSA, D-600, DSL06 LEVITON: 6674, 6672, RDL06, 752-DSM10, IPL06.

#### FEATURES:

- ULTRA SLIM DESIGN Shallow depth makes for easier installation, especially in low-clearance applications. No housing is required. Use these 6-Inch round fixtures for new facilities or as a retrofit replacement for existing recessed lighting.
- COLOR TEMPERATURE TUNABLE This dimmable fixture put out a bright 950 lumen and allow you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located on the back of the fixture.
- DIMMABLE LED Fixture can be dimmed (100%-10%) when installed with an LED compatible dimmer. Output is a bright 950 lumens (75 watt equivalent) while only using 12 Watts of electricity. Instant on with no flickering or buzzing like fluorescent bulbs. High color rendering at 90 CRI. Tested Compatible Dimmers: LUTRON: DVELV-300P-WH, PWCL-153PH, DVCL-153P, CTCL-153P, S-600H-WH-CSA, D-600, DSL06 LEVITON: 6674, 6672, RDL06, 752-DSM10. IPL06.
- ENERGY EFFICIENT & LONG LIFE LED technology





# SPECIFICATIONS:

#### **General Characteristics**

Average Rated Hours

**Finish** 

Average Life Span Years

Dimmable

**Dimming Type** 

**Dimming Percentage** 

Material

Lens Material

Lens Finish

**Electrical Characteristics** 

Watts 12

**Volts** Equivalent Wattage

LED Chip Manufacturer

Power Factor **Temperature** 

Light Characteristics

Lumens Brightness

Color Rendering Index CRI

**Emitted Color** 

Color Temperature Kelvin

Beam Angle Flicker

Fixture Characteristics

Shape

**Number of Lights** 

Mounting Recessed

IC Rating

Fixture Technology

Use Location

Additional Features

Safety Rating Mark

Energy Star

**Energy Star Number** 

Mercury Free

35000

White

32 Yes

Tri-Mode (Triac, ELV, and 0-

10V)

10%-100%

Aluminum & PC

Polycarbonate

White

120

75

0.9

950

90

110°

<30%

Round

1

Yes

**LED** 

Yes

Yes

2397275

Indoor

2835

-4°F - 104°F

CCT Tunable

27K/30K/35K/40K/50K

Package Weight (lb) Cord Length

Size

Case Unit Rate

Item UPC

Warranty Years

6"

(W) 6.81 (H) 1.02 (D) 6.81

(W) 7 (H) 7 (D) 2.5

1

12

6

**Product Data** 

**Product Dimensions** 

Item Dimension (in)

Package Dimension (in)

Pack Size

1 653703877075

5











ETL Listed - Wet Location



# **ACCESSORIES:**

Catalog # 50107-SU TRIM/SDL/6R/BN

Catalog # 50121-SU TRIM/SDL/6R/BK