

Sunlite 87708 LED 4-Inch Square Recessed Slim Downlight, 10 Watts, 650 Lumens, Tunable 27K/30K/35K/40K/50K Color, 90 CRI, Energy Star & ETL Listed, White, for Residential & Commercial Use Slim

DESCRIPTION:

This 4-inch LED Recessed Slim Downlight from Sunlite features innovative technology that allows you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located on the back of the fixture. Its slim feature allows them to be installed in limited clearance areas. Use for new installations or as a retrofit replacement for existing recessed lighting. LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. Comparable output to a 65watt bulb while only using 10 watts of electricity. Estimated annual energy costs of \$1.20 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Built-in long-life LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. This fixture is ETL Listed for Wet Location Installation. Good for commercial or residential installations. Suitable for entryways, bedrooms, kitchens, hallways, bathrooms, and more. Tested Compatible Dimmers: LUTRON: DVELV-300P-WH, PWCL-153PH, DVCL-153P, CTCL-153P, S-600H-WH-CSA, D-600, DSL06 LEVITON: 6674, 6672, RDL06, 752-DSM10, IPL06.

FEATURES:

- ULTRA SLIM DESIGN Shallow depth makes for easier installation, especially in low-clearance applications. No housing is required. Use these 4-Inch square fixtures for new facilities or as a retrofit replacement for existing recessed lighting.
- COLOR TEMPERATURE TUNABLE This dimmable fixture put out a bright 650 lumen and allow you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located on the back of the fixture.
- DIMMABLE LED Fixture can be dimmed (100%-10%)
 when installed with an LED compatible dimmer. Output is a
 bright 650 lumens (65 watt equivalent) while only using 10



no flickering or buzzing ndering at 90 CRI. RON: DVELV-300P-WH, 153P, S-600H-WH-14, 6672, RDL06, 752-

E - LED technology

means 35,000 hours of maintenance-free service. No





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours Finish

Average Life Span Years Ingress Protection

Dimmable
Dimming Type

Dimming Percentage

Material Lens Finish Square 35000 White 32

IP20 (12.5 mm solids, Not protected from liquids)

Yes

Tri-Mode (Triac, ELV, and 0-

10V) 10%-100%

Iron Frosted

30%

Product Dimensions

 Size
 4"

 Diameter (in)
 4.72

 Item Dimension (in)
 (W) 4.72 (H) 1 (D) 4.72

 Package Dimension (in)
 (W) 5.62 (H) 5 (D) 2.62

 Package Weight (lb)
 0.79

Product Data

Case Unit Rate Item UPC Warranty Years 6

653703877082

5

Electrical Characteristics

 Watts
 10

 Volts
 120

 LED Chip Manufacturer
 SMD2835

 Power Factor
 0.9

 Temperature
 -20~40

Light Characteristics

Lumens Brightness650Color Rendering Index CRI90Emitted ColorCCT TunableColor Temperature Kelvin27K/30K/35K/40K/50KBeam Angle110°

Fixture Characteristics

Flicker

ShapeRoundNumber of Lights1MountingRecessedFixture TechnologyLEDUse LocationIndoor

Additional Features

Safety Rating Mark
Safety Rated For Canada
Finergy Star
Finergy Star Number
Wercury Free

ETL Listed - Wet Location
Yes
2397274
Yes











ACCESSORIES:

Catalog # 50108-SU TRIM/SDL/4S/BN

Catalog # 50122-SU TRIM/SDL/4S/BK