

Sunlite 87709 LED 6-Inch Square Recessed Slim Downlight, 12 Watts (75W=), 950 Lumens, Tunable 27K/30K/35K/40K/50K Color, 90 CRI, Energy Star & ETL Listed, White, for Residential & Commercial Use Slim

### **DESCRIPTION:**

This 6-inch LED Recessed Slim Downlight from Sunlite features innovative technology that allows you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference. using a switch located on the back of the fixture. Its slim feature allows them to be installed in limited clearance areas. Use for new installations or as a retrofit replacement for existing recessed lighting. LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. Comparable output to a 75watt bulb while only using 12 watts of electricity. Estimated annual energy costs of \$1.45 (Based on 3 Hrs/Day at \$0.11/kWh). Installing these Energy Star Certified fixtures may qualify you for state or local energy rebates. Built-in long-life LED technology means 35,000 hours of maintenance-free service. No ladders to climb or difficult-to-reach bulbs to replace. This fixture is ETL Listed for Wet Location Installation. Good for commercial or residential installations. Suitable for entryways, bedrooms, kitchens, hallways, bathrooms, and more. Tested Compatible Dimmers: LUTRON: DVELV-300P-WH, PWCL-153PH, DVCL-153P, CTCL-153P, CTCL-153P, D-600, DSL06 LEVITON: 6674, 6672, RDL06, 752-DSM10, IPL06.

#### FEATURES:

- ULTRA SLIM DESIGN Shallow depth makes for easier installation, especially in low-clearance applications. No housing is required. Use these 6-Inch square fixtures for new facilities or as a retrofit replacement for existing recessed lighting.
- COLOR TEMPERATURE TUNABLE This dimmable fixture put out a bright 950 lumen and allow you to choose the color temperature at the time of installation. Tunable 27K/30K/35K/40K/50K color, depending on your preference, using a switch located on the back of the fixture.
- DIMMABLE LED Fixture can be dimmed (100%-10%)



tible dimmer. Output is a net) while only using 12 no flickering or buzzing ndering at 90 CRI. RON: DVELV-300P-WH, 153P, CTCL-153P, DRDL06, 752-DSM10,

ENERGY EFFICIENT & LONG LIFE - LED technology





## SPECIFICATIONS:

#### **General Characteristics**

Average Rated Hours

**Finish** 

Average Life Span Years

Dimmable

**Dimming Type** 

**Dimming Percentage** 

Material

Lens Material

Lens Finish

Application

**Electrical Characteristics** 

Watts

Volts

Equivalent Wattage

Power Factor

**Light Characteristics** 

Lumens Brightness

Color Rendering Index CRI

**Emitted Color** 

Color Temperature Kelvin

Beam Angle

Flicker

Fixture Characteristics

Shape

**Number of Lights** 

Mounting

IC Rating

Fixture Technology

**Use Location** 

Additional Features

Safety Rating Mark

Energy Star Number

Mercury Free

**Energy Star** 

35000

White

32 Yes

Tri-Mode (Triac, ELV, and 0-

10V)

10%-100%

Aluminum & PC

Polycarbonate

White

12

120

75

0.9

950

90

110°

<30%

Square

**LED** 

Yes 2397276

Yes

Indoor

Recessed Yes

CCT Tunable

27K/30K/35K/40K/50K

Residential

**Product Dimensions** 

Size

Item Dimension (in) Package Dimension (in)

Package Weight (lb)

Cord Length

**Product Data** 

Pack Size

Warranty Years

6"

(W) 6.85 (H) 1.02 (D) 6.85

(W) 7.87 (H) 7 (D) 2.37

1.06

12"

Case Unit Rate

Item UPC

653703877099

6

1

5











ETL Listed - Wet Location



# **ACCESSORIES:**

Catalog # 50109-SU TRIM/SDL/6S/BN

Catalog # 50123-SU TRIM/SDL/6S/BK