

Plug-In

Sunlite 88271-SU LED PLD Light Bulb, 9 Watts (26W Equivalent), 950 Lumens, G24q Base, Ballast Dependant, CFL Replacement, UL Listed, 30K - Warm White 1 Pack

Plug and Play

DESCRIPTION:

Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with 3000K color temperature at 3000K. Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.



- UPGRADE TO LED Replace your 26 watt compact fluorescent PL bulbs with energy efficient 9 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 270 degree beam angle that can be rotated at the base for optimal coverage.
- NO FLICKERING OR BUZZING LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 950 lumen with Warm White color temperature at 3000K.
- ENERGY EFFICIENT These 9 watt LED bulbs are direct replacements for 26 watt CFL bulb. That's a 65% energy savings. Low annual operating costs of only \$1.08. (Based on 3 Hours/Day at \$0.11/kWh)
- LONG LIFE SPAN Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- A SAFER CHOICE Unlike CFL bulbs these LED lamps contain no hazardous chemicals. They work with your existing ballasts so no special wiring or modifications are needed. They are UL Listed for damp location installation and DLC Listed for quality and efficiency.





SPECIFICATIONS:

General Characteristics

Bulb Shape Average Rated Hours **Finish** Base

Average Life Span Years Dimmable

Material

Electrical Characteristics

Watts **Equivalent Wattage Power Factor Temperature**

Light Characteristics

Lumens Brightness Color Rendering Index CRI

Emitted Color Color Temperature Kelvin

Beam Angle

Additional Features

Safety Rating Mark **UL Rated Enclosed Fixtures**

DLC

DLC Number

DLC Classification

PLD 50000

White

4-Pin LED Base (G24q)

46 No Plastic

9 18 0.9

-20° to 45° C

950

82

Warm White

3000K 270°

UL Listed - Damp Location

Yes Yes

PL7UM4E2B75T

Standard

Product Dimensions

MOL (in) Item Dimension (in) Item Weight (Ib) Package Dimension (in) Package Weight (lb)

Product Data

Case Unit Rate Pack Size Item UPC Warranty Years Package Type

6.57

(W) 1.34 (H) 6.61 (D) 1.4

0.170

(W) 1.53 (H) 1.53 (D) 7.54

0.250

12

653703882710 5

Вох



