

Plug-In

Sunlite 88278-SU LED Plug & Play PL Horizontal Light Bulb, 16 Watts (42W CFL Replacement), G24q Base, Ballast Dependent, DLC Listed, 40K - Cool White 1 Pack

Plug and Play

DESCRIPTION:

Replace your 42 watt compact fluorescent PL bulbs with energy efficient 16 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 120 degree beam angle that can be rotated at the base for optimal coverage. LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Conveniently compatible with Gx24q, G24q-1, G24q-2, G24q-3, Gx24q-3, Gx24q-4. DLC Listed for quality and efficiency.

FEATURES:

- **UPGRADE TO LED** - Replace your 42 watt compact fluorescent PL bulbs with energy efficient 16 watt LED bulbs from Sunlite. These 4-Pin base (G24q) bulbs are plug and play with no ballast bypass required. 120 degree beam angle that can be rotated at the base for optimal coverage. Ideal replacement for a G24q-1, G24q-2 or G24q-3 base bulb. Compatible with Gx24q, Gx24q-2, Gx24-3, Gx24-4.
- **NO FLICKERING OR BUZZING** - LED Technology means flicker free light that comes on instantly with no warm-up time and no buzzing like CFL bulbs. Output is a bright 1850 lumen with cool white color temperature at 4000K.
- **ENERGY EFFICIENT** - These 16 watt LED bulbs are direct replacements for 42 watt CFL bulb. That's a 61% energy savings. Low annual operating costs of only \$1.93. (Based on 3 Hours/Day at \$0.11/kWh)
- **LONG LIFE SPAN** - Provides up to 50,000 hours of energy efficient light means you'll have to replace difficult to access bulbs less often. Makes commercial and residential fixtures virtually maintenance-free.
- **DLC LISTED** - DLC Listed for quality and efficiency. Bulb measures 1.6-inches wide, 1.7-inches wide, 6.4-inches high.



SPECIFICATIONS:

General Characteristics

Bulb Shape	PL
Average Rated Hours	50000
Finish	White
Base	4-Pin LED Base (G24q)
Average Life Span Years	46
Ingress Protection	IP20 (12.5 mm solids, Not protected from liquids)
Dimmable	No
Material	Plastic

Electrical Characteristics

Watts	16
Equivalent Wattage	26
LED Chip Manufacturer	Type A
Power Factor	0.9
Temperature	-20-45°

Light Characteristics

Lumens Brightness	1850
Color Rendering Index CRI	82
Emitted Color	Cool White
Color Temperature Kelvin	4000K
Beam Angle	120°

Additional Features

Safety Rating Mark	ETL - Damp Location
DLC	Yes
DLC Number	PLSMK20Z61KE
DLC Classification	Standard

Product Dimensions

MOL (in)	6.35
Item Dimension (in)	(W) 1.6 (H) 6.4 (D) 1.7
Package Dimension (in)	(W) 1.9 (H) 1.7 (D) 6.7
Package Weight (lb)	0.350

Product Data

Case Unit Rate	12
Pack Size	1
Item UPC	653703882789
Warranty Years	5
Package Type	Box



VARIATIONS:



88278-SU



88277-SU

<i>Item Number</i>	<i>Description</i>	<i>Watts</i>	<i>Eq Watts</i>	<i>Lumens</i>	<i>CRI</i>	<i>Kelvin Color</i>	<i>Hours</i>	<i>Pack</i>
88278-SU	PLT/G24q/LED/IS/16W/40K	16	26	1850	82	4000K CW	50000	1
88277-SU	PLT/G24q/LED/IS/16W/35K	16	26	1750	82	3500K NW	50000	1